


NEW MEXICO OIL CONSERVATION COMMISSION

MISCELLANEOUS REPORTS ON WELLS



Submit this report in triplicate to the Oil Conservation Commission District Office within ten days after the work specified is completed. It should be signed and filed as a report on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF	<input checked="" type="checkbox"/>	REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL			

June 9, 1952

Farmington, New Mexico

Date

Place

Following is a report on the work done and the results obtained under the heading noted above at the

Turner State Well No. 1 in the
 SW 1/4 Company or Operator Lease 30N R. 9W N. M. P. M.,
 of Sec. 2 T. 30N R. 9W N. M. P. M.,
 Blanco Pool San Juan County.

The dates of this work were as follows: June 2 - 3, 1952.

Notice of intention to do the work was (was not) submitted on Form C-102 on _____, 19____, and approval of the proposed plan was (was not) obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

On June 2, 1952, ran total of 108 joints (4,466.79') 7" OD 8 rd. thd. 20# J-55 Rg. #3 J. & L. casing. Set at 4,438' and cemented with 150 sacks Bridget and 50 Sacks Ideal Regular. Pumped plug to 4,394'. Plug down at 4:00 p.m.

Opened HOWCO DV tool and circulated thru DV tool in preparation for 2nd stage cement job.

On June 3, 1952, cemented with 275 sacks Ideal Regular Cement through HOWCO DV tool - starting at 3,000 feet. Completed this second stage cement job at 1:30 a.m. - June 3, 1952.

On June 5th found Plug No. 1 at 1,420 feet. Drilled some 50 feet into cement. Pressured up pipe to 1,000 lbs. and found everything O.K. Hit No. 2 plug at 4,396 feet. Drilled same, and proceeded to drill 6-1/4" hole "with gas".

Witnessed by Raymond L. Davis McConnell Drilling Corporation To 1 Pusher
 Name Company Title

APPROVED:
 OIL CONSERVATION COMMISSION

Oil and Gas Inspector Dist. #3.

JUN 11 1952

Date

Name

Title

I hereby swear or affirm that the information given above is true and correct.

Name

J. Deason Neal - Agent in Farmington

Position

Representing J. Glen Turner

Company or Operator

Address 1711 Mercantile Bank Building
 Dallas 1, Texas.