



AREA 640 ACRES
LOCATE WELL CORRECTLY

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

WELL RECORD

Mail to District Office, Oil Conservation Commission, to which Form C-101 was sent not later than twenty days after completion of well. Follow instructions in Rules and Regulations of the Commission. Submit in QUINTUPLICATE. If State Land submit 6 Copies

McKay, Payne, Zachry (Company or Operator) Optagrove (Lease)
Well No. 1, in SE 1/4 of SE 1/4, of Sec. 2, T. 30N, R. 12W, NMPM.
Aztec PC Pool, San Juan County.
Well is 790 feet from East line and 790 feet from South line of Section 2. If State Land the Oil and Gas Lease No. is
Drilling Commenced 6/6/58, 19 Drilling was Completed 6/14/58, 19
Name of Drilling Contractor Empire States Drilling Corp.
Address 1020 Simms Building, Albuquerque, New Mexico
Elevation above sea level at Top of Tubing Head 5717 The information given is to be kept confidential until 19

OIL SANDS OR ZONES

No. 1, from 2066 to 2150 PC No. 4, from to
No. 2, from to No. 5, from to
No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.
No. 1, from to feet
No. 2, from to feet
No. 3, from to feet
No. 4, from to feet

CASING RECORD

SIZE	WEIGHT PER FOOT	NEW OR USED	AMOUNT	KIND OF SHOE	CUT AND PULLED FROM	PERFORATIONS	PURPOSE
8-5/8	24	New	102	Larkin			Surface
5 1/2	14	New	2200	Larkin			Producing
1		New	2072				

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
12 1/4	8-5/8	103	100	Halliburton		
7-7/8	5 1/2	2199	150	Halliburton		

RECORD OF PRODUCTION AND STIMULATION

(Record the Process used, No. of Qts. or Gals. used, interval treated or shot.)

Perforated casing from 2068' to 2080' using 3 shots per foot. San frac. with 20,000 lbs. sand and 800 bbls. water.

Result of Production Stimulation
Depth Cleaned Out



