

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other

2. NAME OF OPERATOR  
Amoco Production Company

3. ADDRESS OF OPERATOR  
501 Airport Dr., Farmington, NM 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1095' FSL x 975' FWL

AT TOP PROD. INTERVAL: Same

AT TOTAL DEPTH: Same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐

SUBSEQUENT REPORT OF:

☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐

(other) Squeeze Mesaverde Perforations.

5. LEASE  
SF-081239

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME  
L. C. Kelly

9. WELL NO.

4

10. FIELD OR WILDCAT NAME  
Basin Dakota

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
SW/4, SW/4, Section 3  
T30N, R12W

12. COUNTY OR PARISH  
San Juan

13. STATE

New Mexico

14. API NO.  
30-045-09830

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
5861' G.L.

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Amoco Production Company proposes to cement squeeze the Mesaverde perforations in the above mentioned well as follows:

- (1) Trip in hole with a retrievable bridge plug, tubing, and packer to isolate Mesaverde perforations from 4535'-4575'.
- (2) Squeeze perforations, wait on cement, and drill out cement to bridge plug.
- (3) Retrieve bridge plug.
- (4) Drill out Baker Model "D" packer set at 6580'.
- (5) Commence workover operations as per Sundry Notice 8-25-81. Verbal approval from Richard Bell (USGS) to D. W. Schott (Amoco) on 9-30-81.

Subsurface Safety Valve: Manu. and Type

Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Original Signed By \_\_\_\_\_ TITLE Dist. Admin. Supvr DATE September 30, 1981  
E. E. SVOBODA

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

OCT 9 1981