
Form	9-881	a
(Feb	. 1951)	



(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Land Office SF
Lease No 081226
Unit riorseshoe Canyon

NOTICE OF INTENTION TO DRILL		SURSEOU	ENT REPORT OF WATER SHU		x
NOTICE OF INTENTION TO CHANGE P			ENT REPORT OF SHOOTING (
NOTICE OF INTENTION TO TEST WATE			ENT REPORT OF ALTERING C	_	1 1
NOTICE OF INTENTION TO RE-DRILL	OR REPAIR WELL	1 11	ENT REPORT OF RE-DRILLING		
NOTICE OF INTENTION TO SHOOT OR	ACIDIZE				
NOTICE OF INTENTION TO PULL OR A	ALTER CASING	l ii	ENTARY WELL HISTORY		
NOTICE OF INTENTION TO ABANDON	WELL				-
(INDICA:	TE ABOVE BY CHECK I	MARK NATURE OF REP	PORT, NOTICE, OR OTHER DAT	A)	
•			January I.	* <u>1</u>	950
				 ال	IN 1
ll No. 13 is locat	ed 660 ft. f	$rom_{-} \left\{ S \right\}$ line a	and 3300 ft. from	line of sec.	JEOGI:
R SW/4 Sec. 4	30N	16W	NMPM	PANNING	ION.
(1/2 Sec. and Sec. No.)	(Twp.)	(Range) n juan	(Meridian)	Mexico	
(Field)	(Cor	unty or Subdivision)	(Sta	te or Territory)	-
		TAILS OF WO			
uary II, 1959 Total De Ran 29 joints 5	objective sands; she ing points, and epth 1256'.	ow sizes, weights, and all other important	lengths of proposed casings proposed work) ag (1240°) set at		
tate names of and expected depths to nuary 11, 1959 Total De Ran 29 joints 5 gular cement, 50 sacks Held 1000#/30	epth 1256°. -1/2", 15.50 Formix, 4%	ow sizes, weights, and all other important	lengths of proposed casings proposed work) ag (1240°) set at		
nuary II, 1959 Total De Ran 29 joints 5 gular cement, 50 sacks	epth 1256'1/2", 15.50 Formix, 4%	ow sizes, weights, and all other important 14, J-55 Casis gel., 1/4# F	lengths of proposed casings proposed work) ag (1240°) set at locele per sack.	1250' with 50 se	
uary 11, 1959 Total De Ran 29 joints 5 gular cement, 50 sacks Held 1000#/30	epth 1256'1/2", 15.50 Formix, 4%	ow sizes, weights, and all other important 14, J-55 Casis gel., 1/4# F	lengths of proposed casings proposed work) ag (1240°) set at locele per sack.		
Ran 29 joints 5 gular cement, 50 sacks Held 1000#/30 Top of cament	epth 1256'. 1/2", 15.50 Pozmix, 4% Minutes. by temperatu	waizes, weights, and it all other important #, J-55 Casis gel., 1/4# F	lengths of proposed casings proposed work) ag (1240°) set at locele per sack.	1250' with 50 s. (TEVE) JAN 1 6 1959 DIL CON CO	ACKS
Ran 29 joints 5 gular cement, 50 sacks lield 1000#/30 Top of cament	epth 1256'. -1/2", 15.50's Formix, 4% Minutes. by temperatu	waizes, weights, and it all other important #, J-55 Casis gel., 1/4# F	lengths of proposed casings proposed work) ag (1240°) set at locele per sack.	1250' with 50 s. (TEVE) JAN 1 6 1959 DIL CON CO	ACKS

Title Petroleum Engineer

to the second of the second of

q. N.

Radian Company of the Company of the Company