



(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Santa Fe
Lease No. 061226-B
Unit Bolack

SUNDRY NOTICES AND REPORTS ON WELLS

| | | | |
|--|--|--|-------------------------------------|
| NOTICE OF INTENTION TO DRILL | | SUBSEQUENT REPORT OF WATER SHUT-OFF | <input checked="" type="checkbox"/> |
| NOTICE OF INTENTION TO CHANGE PLANS | | SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING | |
| NOTICE OF INTENTION TO TEST WATER SHUT-OFF | | SUBSEQUENT REPORT OF ALTERING CASING | |
| NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL | | SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR | |
| NOTICE OF INTENTION TO SHOOT OR ACIDIZE | | SUBSEQUENT REPORT OF ABANDONMENT | |
| NOTICE OF INTENTION TO PULL OR ALTER CASING | | SUPPLEMENTARY WELL HISTORY | |
| NOTICE OF INTENTION TO ABANDON WELL | | | |

RECEIVED
JUL 15 1957
U. S. GEOLOGICAL SURVEY
FARMINGTON, NEW MEXICO

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

July 15th, 19 57

Well No. 3 is located 1820 ft. from [M] line and 2130 ft. from [E] line of sec. 4

R1/4 SE 1/4 Sec. 4
(1/4 Sec. and Sec. No.)

TOW
(Twp.)

15N
(Range)

T. 1 N. P. M.
(Meridian)

Hummed
(Field)

San Juan
(County or Subdivision)

New Mexico
(State or Territory)

The elevation of the derrick floor above sea level is 5353 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

6-15-57 TD 90' RKB. Set 2 joints 80' of 8-5/8" OD 24# Spiral Weld casing at 90' RKB with 80 sacks cement, circulated to surface.

6-24-57 Pressured up on casing to 500#. No pressure decrease in 30 minutes.



I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company TOM BOLACK
Address 1010 North Dustin
Farmington, New Mexico

By [Signature]
Title _____

