UNITED STATES

DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELL	SUNDRY	NOTICES	AND	REPORTS	ON	WELLS
------------------------------------	--------	---------	-----	---------	----	-------

'Do not use this form for proposals to drill or to deepen or blug back to a different reservoir, Use Form 9-331-3 for such proposais.)

- gas Infection other 4 a. 2. NAME OF OPERATOR ARCO Oil and Gas Co., a Division of Atlantic Richfield Company
- 3. ADDRESS OF OPERATOR 707 17th Street, P.O. Box 5540, Denver, Colo. 30217
- 4. LOCATION OF WELL REPORT LOCATION CLEARLY. See space 17 Unit J, below.) AT SURFACE: 1980' FSL & 1980' FEL, Sec. 5 AT TOP PROD. INTERVAL: AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE. REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO: TEST WATER SHUT-OFF FRACTURE TREAT

SHOOT OR ACIDIZE REPAIR WELL

PULL OR ALTER CASING

MULTIPLE COMPLETE

CHANGE ZONES ABANDON*

(other)

SUBSEQUENT REF

Form Approved.

5. LEASE

- 14-20-603-733
- 6. IF INDIAN, ALLOTTEE OR TRIBE NAME Navajo
- 7. UNIT AGREEMENT NAME Horseshoe Gallup Unit
- 8. FARM OR LEASE NAME Horseshoe Gallup Unit
- 9. WELL NO.

137

- 10. FIELD OR WILDOAT NAME Hor**s**eshoe Gallup
- 11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
 - Sec. 5-30N-16W
- 12. COUNTY OR PARISH 13. STATE
 - New Mexico <u>San Juan</u>
- 14. API NO.

None Assigned TIONS (SHOW DE, KDB, AND WD)

5299' GR

OGICAL N. McHante on For

1983 JAN 7

U. S. GEOLOGICAL SURVEY, FARMINGTON, N. M.

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* \$11-1-82

This notice supercedes our Sundry Notice Sdated August 31, 1982 on the subject well.

ARCO now proposes to plug and abandon this well, as per the attached revised P & A Procedure.

(This is in compliance with the requirements as set forth in a memorandum dated September 30, 1981, and a subsequent letter of April 26, 1982 , both from the State of New Mexico, Energy and Minerals Department, Oil Conservation Division(copies attached to our August 31, 1982 Sundry Notice).

Subsurface Safety Valve: Manu. and Type		Set @ Ft.
18. I hereby certify that the foregoing is true		December 30
SIGNED Stephen Kose Jan	/ TITLE Dist.Prod.Supt.	-DATE November 1, 1982
	This space for Federal or State office use)	DECEINED
CONDITIONS OF APPROVAL IF ANY:		JAN 1 71983
15. For Hell	NMOCC	C'I C''I C'''.
	*See Instructions on Reverse Side	Dist

HORSESHOE GALLUP UNIT INJECTION WELLS PLUGGING AND ABANDONMENT PROCEDURE (REVISED)

- 1. MIRU.
- 2. Release packer and pull tubing and packer out of hole.
- 3. RIH with tbg open-ended to below the bottom perforation and pump sufficient cement to cover top perforation by 50' inside the casing.
- 4. POH w/tbg. GIH w/wireline and shoot enough holes in production string opposite 150' above top perforation to allow cement squeezing of zone. (This may be necessary since the original cement job may not have covered the Gallup formation by 50'). Squeeze sufficient cement to place a 100' plug outside the casing. Also, leave a 100' plug inside the casing. If unable to squeeze plug outside the casing, leave a 100' plug inside the casing.
- 5. POH w/tbg. GIH w/wireline and shoot enough holes in production casing opposite a point 50' below the surface casing shoe to allow squeezing cement.
- 6. RIH w/tbg open-ended and perform a braden-head squeeze of the perforations. Use sufficient cement for a 100' column behind the casing and a 100' plug inside the casing.
- 7. POH, cut casing one foot below ground level, place a 30' cement plug inside casing, weld on a blind flange, weld a dry hole marker on the blind flange, fill hole and move off.
- 8. Rehabilitate location and access road using stipulations supplied by the surface management agency.

NOTE: BOP's will not be needed in most cases because expected reservoir pressure of the Gallup in the area of abandonment is very low. (Estimated at less than 250 - 300 psi bottom-hole.) If pressure does exist on any of the subject wells, bleed it off, install BOP's if needed, and commence with above procedure.



40. No. 217

TABLE I

Horeshoe Gallup Unit Federal Lease No. 14-08-001-8200 San Juan County, New Mexico.

List of Wells

	NC.	26 -	3_	
	:io-	2 9	-	
3.	No.	103	А	
4.	No.	105	A	
5.	No.	113	A	
), 6.	No:	126		
7.	No.	130	C	
8.	No.	132	C	
9.	No.	135	C	
10.	No.	137	C	
11.	No.	139	C	
12.	No.	141	C	
13.	No.	143	D	
14.	No.	145	D	
15.	No.	148	D	
16.	No.	150	D	
17.	No.	152	D	
18.	No.	154	D	
19.	No.	156	D	
20.	-1104	-160	<u> </u>	

21.	No. 215	D D				41.	No.	223	D
-22.	-No. 162	- 				42.	No.	225	D
23.	No. 164	5			(State	43.	No.	227	D
-24	No. 169	-) -		٠		44.	No.	229	D
25.	No. 171	D.				45.	No.	238	D
26.	No. 173	D			(সমাত	46.	No.	240	D
27.	No. 175	D				47.	No.	248	D
-33	No. 180	-D	•			48.	No.	250	D
		D	are man					259	
30.	No. 184	O				50.	No.	 2 61	C
		٥				51.	No.	263	C
-32	No. 192	-p-				52.	No.	269	C
	No. 194	_				53.	No.	274	c
	No. 196	_				54.	No.	275	C
	No. 201	-0-				55.	No.	73	Ą
36.	No. 203	D				- 56.	No.	-199	-
37.	No. 205	_				-57.	No.	211	D
38.				·		 1			
	No. 213	_	,	g		, 55±			

OIL COM. DIV.