Form Approved. Budget Bureau No. 42-R1424

## UNITED STATES DEPARTMENT OF THE INTERIOR 1 2 1983

14- 20-603-4909 8. IF INDIAN, ALLOTTEE OR TRIBE NAME

GEOLOGICAL SURVEY)

Navajo

## SUNDRY NOTICES AND REPORTS

7. UNIT AGREEMENT NAME Horseshce Gallup Unit

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir, Use Form 9-331-C for such proposals.)

8. FARM OR LEASE NAME Horseshoe Gallup Unit

335 1. pil Infection weii 😅 other well

9. WELL NO.

2. NAME OF OPERATOR ARCO Oil and Gas Co., a rision of Atlantic Richfield Company

250 10. FIELD OR WILDCAT NAME Horseshoe Gallup

3. ADDRESS OF OPERATOR 707 - 17th Street, P.O. Box 5540, Denver, Colo. 30217

11. SEC., T., R., M., OR BLK, AND SURVEY OR

4. LOCATION OF WELL (REPORT LOCATION CLEARLY, See space 17 Unit L, AT SURFACE: 1980' FSL & 660' FWL, Sec. 2

Sec. 2-30N-16W 12. COUNTY OR PARISH 13. STATE

AT TOP PROD. INTERVAL:

New Mexico <u>San Juan</u>

AT TOTAL DEPTH:

14. API NO.

None Assigned

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

ELEVATIONS (SHOW DF, KDB, AND WD) 5643' GR

REQUEST FOR APPROVAL TO: TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL PULL OR ALTER CASING MULTIPLE COMPLETE CHANGE ZONES ABANDON\* (other)

Marine Comment

SUBSEQUENT RE

JAN 07/1983

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent detass GEREOGICA DESCRIPTION date including estimated date of starting any proposed work. If well is directionally drilled, gwentysuriace locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

\$11-1-82

This notice supercedes our Sundry Notice Sdated August 31, 1982, on the subject well.

ARCO now proposes to plug and abandon this well, as per the attached revised P & A Procedure.

(This is in compliance with the requirements as set forth in a memorandum dated September 30, 1981, and a subsequent letter of April 26, 1982 , both from the State of New Mexico, Energy and Minerals Department, Oil Conservation Division(copies attached to our August 31, 1982 Sundry Notice).

	-
Subsurface Safety Valve: Manu. and Type	Set @ Ft.
18. I hereby certify that the foregoing is true and correct	December 30
SIGNED Stephen Rose TITLE Dist. Prod. Supt. DATE	November 1, 1982
(This space for Federal or State office use)	
APPROVED BY TITLE DAT	Ε
Anthelle In	

See Instructions on Reverse Side

# HORSESHOE GALLUP UNIT INJECTION WELLS PLUGGING AND ABANDONMENT PROCEDURE (REVISED)

- 1. MIRU.
- 2. Release packer and pull tubing and packer out of hole.
- 3. RIH with tbg open-ended to below the bottom perforation and pump sufficient cement to cover top perforation by 50' inside the casing.
- 4. POH w/tbg. GIH w/wireline and shoot enough holes in production string opposite 150' above top perforation to allow cement squeezing of zone. (This may be necessary since the original cement job may not have covered the Gallup formation by 50'). Squeeze sufficient cement to place a 100' plug outside the casing. Also, leave a 100' plug inside the casing. If unable to squeeze plug outside the casing, leave a 100' plug inside the casing.
- 5. POH w/tbg. GIH w/wireline and shoot enough holes in production casing opposite a point 50' below the surface casing shoe to allow squeezing cement.
- 6. RIH w/tbg open-ended and perform a braden-head squeeze of the perforations. Use sufficient cement for a 100' column behind the casing and a 100' plug inside the casing.
- 7. POH, cut casing one foot below ground level, place a 30' cement plug inside casing, weld on a blind flange, weld a dry hole marker on the blind flange, fill hole and move off.
- 8. Rehabilitate location and access road using stipulations supplied by the surface management agency.
- NOTE: BOP's will not be needed in most cases because expected reservoir pressure of the Gallup in the area of abandonment is very low. (Estimated at less than 250 300 psi bottom-hole.) If pressure does exist on any of the subject wells, bleed it off, install BOP's if needed, and commence with above procedure.

#### TABLE I

Horeshoe Gallup Unit Federal Lease No. 14-08-001-8200 San Juan County, New Mexico.

### List of Wells

		<del>26 -</del> {	3-	
	No.	29 - (	-	
3.	No.	103	А	
4.	No.	105	A	
5.	No.	113	A	
<del>X</del> 6.	No.	126	-	
7.	No.	130	C	
8.	No.	132	C	
9.	No.	135	C	
10.	No.	137	C	
11.	No.	139	C	
12.	No.	141	C	
13.	No.	143	D	
14.	No.	145	D	
15.	No.	148	$\mathcal{D}$	
16.	No.	150	D	
17.	No.	152	D	
18.	No.	154	D	
19.	No.	156	D	
<del>20.</del>	- 110-1	-160	<u> </u>	

21.	No. 2	15	D
-22.	No. 1	62	0
23.	No. 1	64	D
-24	No. 1	69-	<del>-</del>
25.	No. 1	.71	D
26.	No. 1	.73	D
27.	No. 1	.75	D
-28.	No. 1	.90-	<del></del>
29.	No. 1	.82	D
30.	No.	.84	D
31.	No. I	<b>.</b> 86	٥
-32	No.	.92	<del>-D</del>
33.	No.	L94	D.
34.	No.	L96	D
35	No.	201	9
36.	No.	203	D
37.	No.	205	D
38.	No.	207	D
39.	No.	213	<b>Q</b>
40.	No.	217	D

	41.	No.	223	D.
	42.	No.	225	D
(State)	43.	No.	227	D
	44.	No.	229	D
	45.	No.	238	D
(state)	46.	No.	240	D
	47.	No.	248	D
	48.	No.	250	D
	49.	No.	259	D
	50.	No.	261	C
	51.	No.	263	C
	52.	No.	269	C
	53.	No.	274	C
	54.	No.	275	C
	55.	No.	73	A
-	<del>36.</del>	No.	199	0
	<del>-57 .</del>	No:	-211-	D