14-20-603-733

HAUTED STATES

SMILD SIMILS						
DEPARTMENT	OF	THE	INTERIOR			
GEOLOG	ICAL	SUR	IVEY			

GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE CR TRIBE NAME Navajo				
SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-0 for such proposals.)	7. UNIT AGREEMENT NAME HOrseshoe Gallup Unit 8. FARM OR LEASE NAME				
1. on gas other Injection	Horseshoe Gallup Unit 9. WELL NO.				
2. NAME OF OPERATOR ARCO Oil and Gas Co., a	135				
Division of Azlantic Richfield Company	10. FIELD OR WILDCAT NAME				
3. ADDRESS OF SPERATOR 707 - 17th Street,	Horseshoe Gallup				
P.O. Box 3540, Denver, Colo. 80217	11. SEC., T., R., M., OR BLK. AND SURVEY OR				
4. LOCATION OF WELL REPORT LOCATION CLEARLY. See space 17 below.) Unit L,	AREA Sec. 5-30N-16W				
AT SURFACE: 2310' FSL & 990' FWL, Sec. 5	12. COUNTY OR PARISH 13. STATE				
AT TOP PROD. INTERVAL:	San Juan New Mexico				
AT TOTAL DEPTH:	14. API NO.				
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	None Assigned				
REPORT, OR OTHER DATA	LEVATIONS (SHOW DF. KDB. AND WD)				
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF					
TEST WATER SHUT-OFF SUBSEQUENT REPORT OF STATE SHOOT OR ACIDIZE REPAIR WELL	14. API NO. None Assigned LEVATIONS (SHOW DF, KDB, AND WD) 5317' GR				
REPAIR WELL PULL OR ALTER CASING MULTIPLE COMPLETE GOVERNMENT MULTIPLE COMPLETE MUL	(NOTER REPORT SUITE OF FAME OF FAME OF FAME OF FAME OF THE				
CHANGE ZONES	JAN 7 1983				

5. LEASE

U. S. GEOLOGICAL SURVEY 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and the medical pertinent details, and the medical pertinent details, and the medical pertinent details. including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations andmeasured and true vertical depths for all markers and zones pertinent to this work.)*

211-1-82 This notice supercedes our Sundry Notices dated August 31, 1982, on the subject well.

ARCO now proposes to plug and abandon this well, as per the attached revised P & A Procedure.


(This is in compliance with the requirements as set forth in a memorandum dated September 30, 1981, and a subsequent letter of April 26, 1982 , both from the State of New Mexico, Energy and Minerals Department, Oil Conservation Division(copies attached to our August 31, 1982 Sundry Notice).

Subsurface Safety Valve: Manu. and Typ	e	Set @ Ft.
18. I hereby certify that the foregoing is		December 30
SIGNED Stephen Rose S. C. Rose	TITLE Dist.Prod.Supt.	November 1, 1982
1 A Park	(This space for Federal or State office use)	WEGGIVER
APPROVED BY	TITLE	Mu zion
- 100	MAGG	JAN 1 7 1983
F. F. J. K.a.		OIL CON. DIV.
www.	*See Instructions on Reverse Side	DIST. 3

HORSESHOE GALLUP UNIT INJECTION WELLS PLUGGING AND ABANDONMENT PROCEDURE (REVISED)

- 1. MIRU.
- 2. Release packer and pull tubing and packer out of hole.
- 3. RIH with tbg open-ended to below the bottom perforation and pump sufficient cement to cover top perforation by 50' inside the casing.
- 4. POH w/tbg. GIH w/wireline and shoot enough holes in production string opposite 150' above top perforation to allow cement squeezing of zone. (This may be necessary since the original cement job may not have covered the Gallup formation by 50'). Squeeze sufficient cement to place a 100' plug outside the casing. Also, leave a 100' plug inside the casing. If unable to squeeze plug outside the casing, leave a 100' plug inside the casing.
- 5. POH w/tbg. GIH w/wireline and shoot enough holes in production casing opposite a point 50' below the surface casing shoe to allow squeezing cement.
- 6. RIH w/tbg open-ended and perform a braden-head squeeze of the perforations. Use sufficient cement for a 100' column behind the casing and a 100' plug inside the casing.
- 7. POH, cut casing one foot below ground level, place a 30' cement plug inside casing, weld on a blind flange, weld a dry hole marker on the blind flange, fill hole and move off.
- 8. Rehabilitate location and access road using stipulations supplied by the surface management agency.

NOTE: BOP's will not be needed in most cases because expected reservoir pressure of the Gallup in the area of abandonment is very low. (Estimated at less than 250 - 300 psi bottom-hole.) If pressure does exist on any of the subject wells, bleed it off, install BOP's if needed, and commence with above procedure.



40. No. 217 D

TABLE I

Horeshoe Gallup Unit Federal Lease No. 14-08-001-8200 San Juan County, New Mexico.

List of Wells

·62		≎6	1_	
	-10	-79		
3.	No.	103	А	
4.	No.	105	A.	
5.	No.	113	A	
X 6.	Ho:	126	-6-	
7.	No.	130	C	
8.	No.	132	C	
9.	No.	135	C	
10.	No.	137	C	
11.	No.	139	Ç	
12.	No.	141	C	
13.	No.	143	D	
14.	No.	145	D	
15.	No.	148	D	
16.	No.	150	D	
17.	No.	152	\mathcal{D}	
18.	No.	154	D	
19.	No.	156	D	
20.	-110-	-160	-	

21.	No. 215	9			41.	No.	223	<u>D</u>
22.	No. 162	0			42.	No.	225	D
23.	No. 164	D		(21.t=)	43.	No.	227	D
24.	No. 169	-	•		44.	No.	229	D
25.	No. 171	D			45.	No.	238	D
26.	No. 173	D		(State)	46.	No.	240	D
27.	No. 175	D			47.	No.	248	D
-28	No. 130	-			48.	Nc.	250	D
29.	No. 182	D			49.	No.	259	D
30.	No. 184	D			50.	No.	261	C
31.	No. 186	۵			51.	No.	263	C
-32	No. 192	-0			52.	No.	269	C
33.	No. 194	D			53.	No.	274	c
34.	No. 196	D			54.	No.	275	C
35.	No. 201	9			55.	No.	73	Ą
36.	No. 203	D	=	-	56.	No.	199	-0
37.	No. 205	D			-57 .	No.	211	-D
38.	No. 207	D						
39.	No. 213	Q						

L.J. 3