

3-000

1-EPNG H. L. Kendrick

NEW MEXICO OIL CONSERVATION COMMISSION

SWP-117

1-EPNG Bill Parriah

1-WP Carr, 2-SUG

Form C-122

2-Delhi Taylor

Revised 12-1-55

1-D, 2-F

MULTI-POINT BACK PRESSURE TEST FOR GAS WELLS

Pool Basin Dakota Formation Dakota County San JuanInitial X Annual _____ Special _____ Date of Test 8/20/62Company Southwest Production Co. Lease Rhoda Abrams Well No. 2Unit H Sec. 5 Twp. 30 N Rge. 11 W Purchaser El Paso Natural Gas CompanyCasing 4 1/2" Wt. 10.50 I.D. 4.032 Set at 6941 Perf. 6668 To 6768Tubing 1 1/2" Wt. 2.75 I.D. 1.610 Set at 6772 Perf. _____ To 6772Gas Pay: From 6668 To 6768 L 6772 xG .67 -GL 4537.2 Bar.Press. 12.0Producing Thru: Casing _____ Tubing X Type Well Single-Gas

Single-Bradenhead-G. G. or G.O. Dual

Date of Completion: 8/9/62 Packer _____ Reservoir Temp. _____

OBSERVED DATA

Tested Through (Packer) (Choke) (Meters) Type Taps _____

No.	Flow Data					Tubing Data		Casing Data		Duration of Flow Hr.
	(Prover) (Line) Size	(Choke) (6668) Size	Press. psig	Diff. h _w	Temp. °F.	Press. psig	Temp. °F.	Press. psig	Temp. °F.	
SI						2073		2053		7 days
1.		3/4"	108		73	108	73	720		3 hr.
2.										
3.										
4.										
5.										

FLOW CALCULATIONS

No.	Coefficient (24-Hour)	$\sqrt{h_{wpf}}$	Pressure psia	Flow Temp. Factor F _t	Gravity Factor F _g	Compress. Factor F _{pv}	Rate of Flow Q-MCFPD @ 15.025 psia
1.	12.3650		120	.9877	.9463	1.011	1.402
2.							
3.							
4.							
5.							

PRESSURE CALCULATIONS

Gas Liquid Hydrocarbon Ratio _____ cf/bbl.
 Gravity of Liquid Hydrocarbons _____ deg.
 F_c _____ (1-e^{-s})

Specific Gravity Separator Gas _____
 Specific Gravity Flowing Fluid _____
 P_c 2065 P_c² 4264.2
 P_w 732 P_w² 535.8

No.	P _w P _t (psia)	P _t ²	F _c Q	(F _c Q) ²	(F _c Q) ² (1-e ^{-s})	P _w ²	P _c ² -P _w ²	Cal. P _w	P _w P _c
1.						535.8	3728.4		.354
2.									
3.									
4.									
5.									

Absolute Potential: 1,549 MCFPD; n .75COMPANY Southwest Production CompanyADDRESS 207 Petr. Club Plaza, Farmington, New MexicoAGENT and TITLE George L. Hoffman, Production EngineerWITNESSED H. McAnallyCOMPANY El Paso Natural Gas Company

REMARKS

INSTRUCTIONS

This form is to be used for reporting multi-point back pressure tests on gas wells in the State, except those on which special orders are applicable. Three copies of this form and the back pressure curve shall be filed with the Commission at Box 871, Santa Fe.

The log log paper used for plotting the back pressure curve shall be of at least three inch cycles.

NOMENCLATURE

Q = Actual rate of flow at end of flow period at W. H. working pressure (P_w).
MCF/da. @ 15.025 psia and 60° F.

P_c = 72 hour wellhead shut-in casing (or tubing) pressure whichever is greater.
psia

P_w = Static wellhead working pressure as determined at the end of flow period.
(Casing if flowing thru tubing, tubing if flowing thru casing.) psia

P_t = Flowing wellhead pressure (tubing if flowing through tubing, casing if flowing through casing.) psia

P_f = Meter pressure, psia.

h_w = Differential meter pressure, inches water.

F_g = Gravity correction factor.

F_t = Flowing temperature correction factor.

F_{pv} = Supercompressability factor.

n = Slope of back pressure curve.

Note: If P_w cannot be taken because of manner of completion or condition of well, then P_w must be calculated by adding the pressure drop due to friction within the flow string to P_t .