MULTI-POINT BACK PRESSURE TEST FOR GAS WELLS

Special___

4453

жG

1

OBSERVED DATA

FLOW CALCULATIONS

Flow Temp.

Factor

Temp.

or.

Purchaser

Tubing Data

Press.

psig

.700

Formation Bubsts

Company Man Andrews Personal Seas. Lease L. C. Mily Well

L 6683

Packer

Diff.

 $\mathbf{h}_{\mathbf{W}}$

Pressure

Tubing_

Pool Beein Behote

Initial # Annual_

Gas Pay: From 6600 To 6788

Date of Completion: 7-16-64

Tested Through (Choke)

(Choke)

Size

.735

Flow Data

Press.

psig

111

Producing Thru: Casing___

(Line)

Size

Coefficient

& Supe

No.

No.

Unit Sec. Twp. 300 Rge. 1

Casing 4-1/2 Wt. 10.5 I.D. 4.008 Set at 6791

Tubing 2-3/0 Wt. 4.7 I.D. 1.995 Set at_

10	N	COMMISSIO	NC										
							Form C-122						
_						Revi	sed 12-1-55						
TE	ST	FOR GAS	WE	LLS		11012							
County See June													
Date of Test													
		 	_Der	re or	rest								
B.		tily		Well	L No		<u> </u>						
יינול	e b	aser											
		(135	10			673	F-4733						
Perf. 6665-6665 To 6720-6743													
_ P	eı	f.	146	· .	ro	(488						
		_GL	461		Bar.Pre		12						
						-							
~:		Type We	11_				Dual						
51	ne	Le-Brade Reservo	nne ir	au-c. (Temp.	. OP (3.U.							
			•	* -									
ATA		a - 1											
			Ту	pe Tap	s	-	<u> </u>						
د. و	· ·	Dot -		sing D	()	•							
88	-	Data Temp.			Temp.	†	Duration						
		-				•	of Flow						
ile	3	o _F ,	_	sig	F.		Hr.						
T		والمحار التحار	1	367			-3 12.						
_						- -							
	_		-	· · · · · · · · · · · · · · · · · · ·		╂—							
		L		·····	L								
I.)NS	Gravity	 -	Compac	. 1	Pot	e of Flow						
•		Factor		Compress. Factor		Q-MCFPD							
	Fg			Fpv		● 15.025 psia							
		.989		L.CO		2715							
4			-										
+			_										
\Box													
A.	ľI	ONS					•						
	- '			~ •		_ ·							
		Speci	fic fic	Gravi Gravi	ty Sep ty Fla	arat wins	or Gas						
Specific Gravity Flowing Fluid P. 1979 P. 3.936.461													
		y											
_	_	·	1	<u> </u>	1								
		P _w 2		$P_c^2 - P_w^2$	i i	al.	P _w P _c						
_						P _w _	c						
\Box	L												
-	\vdash		╁		+								
	<u> </u>	.75											
- Inth													
- AFITHVIE													

i	(24-Hou	יען ני	$n_{\mathbf{W}} p_{\mathbf{f}}$	psia	psia rt		r pv		• 1)102) psia					
1.	12,3450			231 1.000		, 5233	1.507		2713					
2.														
3.														
4.														
5.														
	PRESSURE CALCULATIONS													
Gas Liquid Hydrocarbon Ratiocf/bbl. Specific Gravity Separator Gas														
No.	P _w Pt (psia)	$P_{\mathbf{t}}^2$	F _c Q	$(F_cQ)^2$	(F _c Q) ² (1-e ^{-s})	P _w 2	P _c -P _w ²	Cal.	P _w P _c					
1. 2. 3. 4. 5.						372, 389	1,24,21							
2.							 							
3.						 	<u> </u>							
4.						 	 							
5.					<u> </u>	<u> </u>	<u> </u>							
Abs	olute Potent	ial:	304	M	MCFPD; n	.75								
	PANY	علاقة ا												
	ress_	. 444, 1	غرواجيو	ing the Steel	40			ATT OF						
	NT and TITLE	7. 5.		Metrict In				(('}\\						
	NESSED	171	Samuel 1	SIGNETORIO				TPI_{1}	<u> - ber</u>					
COM	AGENT and TITLE WITNESSED COMPANY SIGNED REMARKS JUL 29 1964													
					1	JUL 2919	364							
	-				I won con									
					\ \	DIST.	3							
					-									

INSTRUCTIONS

This form is to be used for reporting multi-point back pressure tests on gas wells in the State, except those on which special orders are applicable. Three copies of this form and the back pressure curve shall be filed with the Commission at Box 871, Santa Fe.

The log log paper used for plotting the back pressure curve shall be of at least three inch cycles.

NOMENCLATURE

- Q I Actual rate of flow at end of flow period at W. H. working pressure (P_W) . MCF/da. @ 15.025 psia and 60° F.
- P_c = 72 hour wellhead shut-in casing (or tubing) pressure whichever is greater. psia
- PwT Static wellhead working pressure as determined at the end of flow period. (Casing if flowing thru tubing, tubing if flowing thru casing.) psia
- P_t Flowing wellhead pressure (tubing if flowing through tubing, casing if flowing through casing.) psia
- P_{f} Meter pressure, psia.
- $h_{\mbox{W}}\mbox{\footnote{\o}}$ Differential meter pressure, inches water.
- $F_g = Gravity$ correction factor.
- F_t Flowing temperature correction factor.
- Fpv Supercompressability factor.
- n I Slope of back pressure curve.

Note: If P_{W} cannot be taken because of manner of completion or condition of well, then P_{W} must be calculated by adding the pressure drop due to friction within the flow string to P_{+} .

1.50