


NEW MEXICO OIL CONSERVATION COMMISSION

**MISCELLANEOUS REPORTS ON WELLS**



Submit this report in triplicate to the Oil Conservation Commission District Office within ten days after the work specified is completed. It should be signed and filed as a report on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING
REPORT ON RESULT OF TEST OF CASING SHUT-OFF	<b>X</b>	REPORT ON DEEPENING WELL
REPORT ON RESULT OF PLUGGING OF WELL		

July 15, 1952

Farmington, New Mexico.

Date

Place

Following is a report on the work done and the results obtained under the heading noted above at the \_\_\_\_\_

**Turner** State **2** in the  
Company or Operator Lease Well No.

NE 1/4 of Sec. 2, T. 30N, R. 9W, N. M. P. M.,  
Pool San Juan County.

**Elanco** Pool **San Juan** County.

The dates of this work were as follows: July 8th and July 11th.

Notice of intention to do the work was ~~present~~ submitted on Form C-102 on June 12, 1952, 19\_\_\_\_, and approval of the proposed plan was ~~obtained~~ obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

On July 8th, ran total of 140 joints (4,398.41') of 7" OD, 8 rd. thd., 17#, Range #2, casing. Set at 4,385 feet, and cemented first stage with 200 sacks of Bridget and 50 sacks Ideal regular cement. Pumped plug to 4,320 feet - plug down at 6:20 a.m.

A Temperature Survey found top of cement at 3,100' - 1,285' fill up. Cemented second stage through HOWCO DV Tool at 2,785' with 200 sacks Ideal Regular. Plug down and job completed at 5:30 p.m.

On July 11th, tested casing with 1,000 pounds pressure, and found everything O.K. Drilled float and plug at 2,774' - lower plug at 4,342'. Cleaned out to 4,411'. Started drilling "with gas" at 5:05 p.m., using 6-1/4" bit.

Witnessed by Raymond L. Davis McCormell Drilling Corporation Tool Pusher  
Name Company Title

APPROVED:  
 OIL CONSERVATION COMMISSION

*Al Greer*

Oil and Gas Inspector Dist. #3.

JUL 16 1952

Date

Name

Title

19\_\_\_\_

I hereby swear or affirm that the information given above is true and correct.

*C. Deason Neal*  
 Name C. Deason Neal - Agent in Farmington

Position (P.O. Box 728)

Representing J. Glenn Turner

Company or Operator

Address 1711 Mercantile Bank Building  
Dallas 1, Texas.

SAN JUAN DRILLING COMPANY  
P. O. BOX 728  
FARMINGTON, NEW MEXICO



July 15, 1952

Mr. Al Greer  
Oil and Gas Inspector  
District No. 3  
Oil Conservation Commission  
Aztec, New Mexico.

Re: New Mexico Lease B-10889  
Turner-State No. 2.

Dear Mr. Greer:

Herewith are three copies of your Form C-103, reporting the setting of 7" casing on this well, and the testing of same. It is our understanding that you do not need but three copies of this particular report - but if more are needed, please notify the writer, and we will furnish them.

Please return an "approved" copy to the attention of the writer - Box 728 - Farmington, New Mexico - to be placed in Mr. Turner's files here.

We understand the well is about completed - and will be "shot" in the next day or two. Thereupon, final report will be prepared and furnished you.

We also enclose copy of the "Temperature Survey" made on July 8th for your files.

Very truly yours,

A handwritten signature in cursive script that reads "G. Beeson Neal".

G. Beeson Neal  
For J. Glenn Turner

Copy: Mr. Turner - Dallas.