

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Form approved
August 1966, No. 1
OF MINERAL DESIGNATION AND SURVEY

57-073198

G. A. INDIAN, ALLEGOTTE OF THE MINES

SUNDRY NOTICES AND REPORTS ON WELLS

Inform use this form for reporting on each well or group of wells based on a different reservoir.
SEE APPLICATION FOR PERMIT FOR WELL PRODUCTION

1. NAME OF OPERATOR Nye Oil & Gas Company		2. UNIT AGREEMENT NAME
3. ADDRESS OF OPERATOR P. O. Drawer 570, Farmington, New Mexico		4. NAME OF LEASE NAME Nye
5. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) 910 FNL & 990 FWL, Section 1-30N-11W		6. WELL NO. #9
7. PERMIT NO.		8. FIELD AND POOL, OR WILDCAT
9. ELEVATIONS (SHOW WHETHER LF, RT, CR, ETC.) 5974 Gr		9. FIELD AND POOL, OR WILDCAT Fruitland
10. COUNTY OR PARISH San Juan		11. SEC., T., R., OR ECK, AND SULFUR OR ALMA
12. COUNTY OR PARISH New Mexico		13. SECTION 1-30N-11W

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

WELL SHUT-OFF	PERMITS ON ALTERN. CASING	WELL SHUT-OFF	REPAIRING WELL
WELL TREAT	MULTIPLE COMPLETION	FRACTURE TREATMENT	ALTERING CASING
WELL ENLARGE	ABANDON*	SHOOTING OR ACIDIZING	ABANDONMENT*
WELL WELL	CHANGE PLANS	Other	

RECEIVED
MAY 4 1971
OIL CON. COM.
DIST. 3

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent data and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

- 4-22-71 Moved on workover rig.
- 4-23-71 Rigged up. Found hole in 2-7/8" casing @ 1188'. Worked 2-7/8" Sand pump past hole and cleaned out to 2500'.
- 4-24-71 Set bridge plug @ 2416'. Squeezed hole at 1188' with 50 sacks cement. Pressure 200#.
- 4-25-71 Drilled cement from 1100 to 1225. Cleaned out to 2416'. Ran bond log - bond ok.
- 4-26-71 Spotted 100 gals 7% HCL, perforated from 2414-2440, 4 SPF. Gun hung up in hole, pulled out of rope socket, left rope socket, 3 subs, collar locator in hole. Top of fish @ 2409'. Started in hole with drill pipe & overshot. Well produced approximately 3,000 MCF/D. Pulled drill pipe. Well loaded up with water.
- 4-27-71 No build-up.
- 10-71 Temporarily abandon.

RECEIVED
MAY 3 1971
U. S. GEOLOGICAL SURVEY

18. For use only by District Superintendents and correct

SIGNED [Signature] DISTRICT SUPERINTENDENT DATE April 30, 1971

APPROVED BY _____ TITLE _____ DATE _____

COPIES OF APPROVAL, IF ANY: