Fcrm 3160-5 (November 1983)

REPAIR WELL

(Other)

TATES SUBMIT IN TRIPLICATE !!

Expires August 31, 1985 PAGE DESIGNATION AND ABSILE NO

Form approved.

Budget Bureau No. 1004-6

$(\mathbf{F}o)$	merly 9-331) DEPARIMENT OF THE INTERNOT	verse side)	1	42212
	BUREAU OF LAND MANAGEMENT		14-20-6	
	SUNDRY NOTICES AND REPORTS ON (Do not use this form for proposals to drill or to deepen or plug back to use "APPLICATION FOR PERMIT—" for such proposal	WELLS to a different reservoir.	Navajo	
1.	TY GAR C	MEO TIA ED		
	NELL X WELL OTHER	11017		<u>Gallup Unit</u>
2.	NAME OF OPERATOR	NOV 1 0 1986	8. FARM OR LEASE NAM	IE .
	ARCO Oil and Gas Company	<u></u>		<u>Gallup Unit</u>
3.	ADDRESS OF OPERATOR BUR	EAU OF LAND MANAGEMENT	9. WBLL NO.	
	P. O. Box 1610, Midland, Texas, 79702 FAS	RMINGTON RESOURCE AREA	131	
4.]	P. O. Box 1610, Midland, Texas 79702 FAS COCATION OF WELL (Report location clearly and in accordance with any State See also space 17 below.)	10. FIELD AND POOL OF	WILDCAT	
	At surface Unit " E ",	Horseshoe Gallup		
	1650' FNL & 990' FWL, Sec. 5		11. SBC., T., B., M., OR S SURVEY OR ARMA	BLE. AND
	•	Sec 5-30N-16W		
14.	PERMIT NO 15 ELEVATIONS (Show whether DF, RT, or	12. COUNTY OR PARISH	13. STATE	
No API NO. Assigned 5360' GR			San Juan	N M
16.	Check Appropriate Box To Indicate Natur	e of Notice, Report, or C	Other Data	
	NOTICE OF INTENTION TO:	QUENT REPORT OF:		
	TEST WATER SHUT-OFF PULL OR ALTER CASING	WATER SHCT-OFF	REPAIRING V	WELL
	FRACTUBE TREAT MULTIPLE COMPLETE	FRACTURE TREATMENT	ALTERING C.	ASING
	SHOOT OR ACIDIZE ABANDON*	SHOOTING OR ACIDIZING	ABANDONME	NT* X

Nors: Report results of multiple completion on Well Completion or Recompletion Report and Log form. 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

This well was plugged 10/27/84 - 10/30/84 as follows:

CHANGE PLANS

Plug	<u>Interval</u>	<u>Cement</u>	.v
1	866 - 1131	30 sx	Spotted plug to cover Gallup perfs 1093 - 1131.
2	250 - 350	30 sx	Squeezed 2 perforations at 350' to isolate the TOC from Temp Survey at 500'. Left a 100' cement plug inside the 5-1/2" casing.
3	52 - 152	30 sx	Squeezed 2 perforations at 152' to isolate the surface casing shoe at 103'. Left a 100' plug inside the 5-1/2" casing.
4	0 - 30	5 sx	Spotted a 5 sk plug at surface.

Welded a steel plate over the top & installed a dry hole market. 18. I hereby certify that the foregoing is true and correct 915-688-5672 7-86 TITLE Engr. Tech. Spec. (This space for Federal or State office use) APPROVED BY TITLE CONDITIONS OF APPROVAL, IF ANY: A. C. . . . 67. ton

*See Instructions on Reverse Side