'Do not use this i reservoir, Use For

CHANGE ZONES

private .

ABANDON* (other)

1983

JAN 7

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY	5. LEASE 14-20-603-733 6. IF INDIAN, ALLOTTEE OR TRIBE NAME			
SUNDRY NOTICES AND REPORTS ON WELLS a not use this form far apposals to drill on to deepen or plug back to a different	Navajo 7. UNIT AGPEEMENT NAME Horseshoe Gallup Unit			
eservoir, Use Form 3–331–0 for such proposats.)	8. FARM OR LEASE NAME Horseshoe Gallup Unit			
1. oil \$as other	9. WELL NC. 130			
piwision of Atlantic Richfield Company 3. ADDRESS OF OPERATOR 707 - 17th Street,	10. FIELD OR WILDCAT NAME Horseshoe Gallup			
P.O. Box 5540, Denver, Colo. 30217	11. SEC., T., R., M., OR BUK, AND SURVEY			
4. LOCATION OF WELL REPORT LOCATION CLEARLY. See space 17 pelow. Unit H,	Sec. 6-30N-16W			
AT SURFACE: 1650' FNL & 330' FEL, Sec. 6 AT TOP PROD. NTERVAL:	12. COUNTY OR PARISH 13. STATE San Juan New Mexic			
AT TOTAL DEPTH:	14 40 10			

AT SURFA AT TOP P 0 AT TOTAL DEPT 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, None Assigned EVATIONS (SHOW DF, KDB, AND WD) REPORT, OR OTHER DATA 5352' GR SUBSEQUENT REPORT REQUEST FOR APPROVAL TO: TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL PULL OR ALTER CASING MULTIPLE COMPLETE

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent descriptions descriptions descriptions descriptions and measured and true vertical depths for all markers and zones pertinent to this work.)*

This notice supercedes our Sundry Notice dated August 31, 1982, on the subject well.

ARCO now proposes to plug and abandon this well, as per the attached revised P & A Procedure.

(This is in compliance with the requirements as set forth in a memorandum dated September 30, 1981, and a subsequent letter of April 26, 1982 , both from the State of New Mexico, Energy and Minerals Department, Oil Conservation Division(copies attached to our August 31, 1982 Sundry Notice). MERRINGTE

	F	Un of the D. U. He	A Participant		
Subsurface Safety Valve: Manu. and Type			• • • • • • • • • • • • • • • • • • • •		Ft.
18. I hereby certify that the foregoing is true	e and correct			December 30	
SIGNED Stephen Rose Jun	PTITLE Dis	t.Prod.Supt	DATE _	November 1, 19	82
J. C. NOSE		deral or State office use)			
APPROVED BY	TITLE		DATE		
CONDITIONS OF APPROVAL IF ANY:					
FLIXA		NMOCC*			

*See Instructions on Reverse Side

HORSESHOE GALLUP UNIT INJECTION WELLS PLUGGING AND ABANDONMENT PROCEDURE (REVISED)

- 1. MIRU.
- 2. Release packer and pull tubing and packer out of hole.
- 3. RIH with tbg open-ended to below the bottom perforation and pump sufficient cement to cover top perforation by 50' inside the casing.
- 4. POH w/tbg. GIH w/wireline and shoot enough holes in production string opposite 150' above top perforation to allow cement squeezing of zone. (This may be necessary since the original cement job may not have covered the Gallup formation by 50'). Squeeze sufficient cement to place a 100' plug outside the casing. Also, leave a 100' plug inside the casing. If unable to squeeze plug outside the casing, leave a 100' plug inside the casing.
- 5. POH w/tbg. GIH w/wireline and shoot enough holes in production casing opposite a point 50' below the surface casing shoe to allow squeezing cement.
- 6. RIH w/tbg open-ended and perform a braden-head squeeze of the perforations. Use sufficient cement for a 100' column behind the casing and a 100' plug inside the casing.
- 7. POH, cut casing one foot below ground level, place a 30" cement plug inside casing, weld on a blind flange, weld a dry hole marker on the blind flange, fill hole and move off.
- 8. Rehabilitate location and access road using stipulations supplied by the surface management agency.

NOTE: BOP's will not be needed in most cases because expected reservoir pressure of the Gallup in the area of abandonment is very low. (Estimated at less than 250 - 300 psi bottom-hole.) If pressure does exist on any of the subject wells, bleed it off, install BOP's if needed, and commence with above procedure.




TABLE I

Horeshoe Gallup Unit Federal Lease No. 14-08-001-8200 San Juan County, New Mexico.

list of Wells

	TC.	25 - (!
-2-	No.	29 -	-
3.	No.	103	A
4.	No.	105	A
5.	No.	113	A
% 6	Ho.	126	
7.	No.	130	C
/ B.	No.	132	C
9.	No.	135	C
10.	No.	137	C
11.	No.	139	Ç
12.	No.	141	C
13.	No.	143	D
14.	No.	145	D
15.	No.	148	\mathcal{D}
16.	No.	150	D
17.	No.	152	\mathcal{D}
18.	No.	154	D
19.	No.	156	D
20.	-1104	-160	P

21.	No.	215	Ð.
22.	No.	162	0
23.	No.	164	D
-24.	No.	169	-)-
25.	No.	171	D
26.	No.	173	D
27.	No.	175	D
-38	No.	130-	-
29.	No.	182	D
30.	No.	184	D
31.	No.	186	۵
-32	No.	192	-p
33.	No.	194	D.
34.	No.	196	D
-35	-No-	201	9
36.	No.	203	D
37.	No.	205	D
38.	No.	207	D
39.	No.	213	0
40.	No.	217	D

4	1.	No.	223	D
4	2.	No.	225	D
(State) 4	3.	No.	227	D
4	4.	No.	229	D
4	5.	No.	238	D
(State) 4	6.	No.	240	D
4	.7 .	No.	248	D
4	8.	No.	250	D
4	9.	No.	259	D
5	10.	No.	261	C
5	il.	No.	263	<u></u>
5	2.	No.	269	C
5	3.	No.	274	C
5	4.	No.	275	C
5	55.	No.	73	Ą
<u>-</u> -	6.	No.	199	0
4	7.	No.	211	D

DECEIVED