UNITED STATES

JAN 12 1983

5. LEASE

DEPARTMENT	OF	THE	INTERIOR CON.	חו
GEOLOGI	CAL	SUR	IVEY DIST	DIV

14-20-603-4908

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

Navajo

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for droposals to drill or to deepen or plug back to a different reservoir. Use form 3-331-0 for such proposals.

- 1. of \square gas \square other Infection
- 2. NAME OF OPERATOR ARCO Oil and Gas Co., a Division of Atlantic Richfield Company
- 3. ADDRESS OF OPERATOR 707 17th Street, P.O. Box 5540, Denver, Colo. 30217
- 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) Unit B, AT SURFACE: 720' FNL & 2040' FEL, Sec. 2 AT TOP PROD. INTERVAL: AT TOTAL DEPTH:
- 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE. REPORT, OR OTHER DATA

7. UNIT AGREEMENT NAME Horseshoe Gallup Unit

8. FARM OR LEASE NAME Horseshoe Gallup Unit

9. WELL NO.

229

- 10. FIELD OR WILDCAT NAME
 Horseshoe Gallup
- SEO., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 2-30N-16W

12. COUNTY OR PARISH 13. STATE
San Juan New Mexico

14. API NO.

None Assigned

15. ELEVATIONS (SHOW DF, KDB, AND WD)

REQUEST FOR APPROVAL TO:
TEST WATER SHUT-OFF
FRACTURE TREAT
SHOOT OR ACIDIZE
REPAIR WELL
PULL OR ALTER CASING
MULTIPLE COMPLETE
CHANGE ZONES
ABANDON*
(other)

SUBSEQUENT REPORT OF

(NOTE: Regart esuits of multiple complete of Bozone

SURVERING IN 19-330.)

SOLOGICAL N. M. CHRV

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

This notice supercedes our Sundry Notices dated August 31, 1982, on the subject well.

ARCO now proposes to plug and abandon this well, as per the attached revised P & A Procedure.

(This is in compliance with the requirements as set forth in a memorandum dated September 30, 1981, and a subsequent letter of April 26, 1982, both from the State of New Mexico, Energy and Minerals Department, Oil Conservation Division(copies attached to our August 31, 1982 Sundry Notice).

Subsurface Safety Valve: Manu. and T) Ft.
18. I hereby certify that the foregoing	is true and correct	Decem	ber 30
18. I hereby certify that the foregoing signed Stephen Kase	TITLE Dist. Prod. S	upt DATE Novembe	r 1 , 1982
	(This space for Federal or State offi	ce use)	
APPROVED BY	TITLE	DATE	
CONDITIONS OF APPROVAL, IF ANY:	MMoon		
7 PCHUM	and CC.		

de 3

J. J. Killin

*See Instructions on Reverse Side

HORSESHOE GALLUP UNIT INJECTION WELLS PLUGGING AND ABANDONMENT PROCEDURE (REVISED)

- 1. MIRU.
- 2. Release packer and pull tubing and packer out of hole.
- 3. RIH with tbg open-ended to below the bottom perforation and pump sufficient cement to cover top perforation by 50' inside the casing.
- 4. POH w/tbg. GIH w/wireline and shoot enough holes in production string opposite 150' above top perforation to allow cement squeezing of zone. (This may be necessary since the original cement job may not have covered the Gallup formation by 50'). Squeeze sufficient cement to place a 100' plug outside the casing. Also, leave a 100' plug inside the casing. If unable to squeeze plug outside the casing, leave a 100' plug inside the casing.
- 5. POH w/tbg. GIH w/wireline and shoot enough holes in production casing opposite a point 50' below the surface casing shoe to allow squeezing cement.
- 6. RIH w/tbg open-ended and perform a braden-head squeeze of the perforations. Use sufficient cement for a 100' column behind the casing and a 100' plug inside the casing.
- 7. POH, cut casing one foot below ground level, place a 30' cement plug inside casing, weld on a blind flange, weld a dry hole marker on the blind flange, fill hole and move off.
- 8. Rehabilitate location and access road using stipulations supplied by the surface management agency.

NOTE: BOP's will not be needed in most cases because expected reservoir pressure of the Gallup in the area of abandonment is very low. (Estimated at less than 250 - 300 psi bottom-hole.) If pressure does exist on any of the subject wells, bleed it off, install BOP's if needed, and commence with above procedure.

TABLE I

Horashoe Gallup Unit Federal Lease No. 14-08-001-8200 San Juan County, New Mexico.

list of Wells

	No.	79 <u> </u>	
	No.		
4.	No.	105	A
5.	No.	113	A
6.	. 10.	126	-
7.	No.	130	C
8.	No.	132	C
9.	No.	135	C
10.	No.	137	C
11.	No.	139	Ç
12.	No.	141	C
13.	No.	143	D
14.	No.	145	D
15.	No.	148	D
16.	No.	150	D
17.	No.	152	\mathcal{D}
18.	No.	154	D
19.	No.	156	D
20.	- 110-	-160	-

		•	•
		•	
21.	No. 215	Ų	
	-No. 162	0	
23.	No. 164	D	
-24	No. 169		
25.	No. 171	D	
26.	No. 173	D	
27.	No. 175	D	
-28.	No. 180	D	
29.	No. 182	0	
30.	No. 184	O	٠.
31.	No. 186	۵	
-32.	No. 192	-0	
33.	No. 194	D.	
34.	No. 196	D	
35.	No. 201	9	
36.	No. 203	D	
37.	No. 205	D	
38.	No. 207	D	
39.	No. 213	Q	
40.	No. 217	D	

	41.	No.	223	2
	42.	No.	225	D
sute)	43.	No.	227	D
	44.	No.	229	D
	45.	No.	238	D
state)	46.	No.	240	D
	47.	No.	248	D
	48.	No.	250	D
	49.	No.	259	D
	50.	No.	261	C
	51.	No.	263	C
	52.	No.	269	C
	53.	No.	274	C
	54.	No.	275	C
	55.	No.	73	Ą
	-36.	-No.	-199	-0
	-57 .	No.	-211	D