

(SUBMIT IN TRIPLICATE)


UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Land Office Santa Fe

Lease No. 079043

Unit Northeast Blance

Unit Agreement No. 1, Sec. 929



SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....
NOTICE OF INTENTION TO ABANDON WELL.....	<u>Subsequent Report of</u> .....

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

June 28, 1957

Well No. 5A-33 is located 2580 ft. from [N] line and 1135 ft. from [E] line

31 1/4 Sec. 33  
(1/4 Sec. and Sec. No.)

31 N 7 W  
(Twp.) (Range)

RPM  
(Meridian)

Blance Monarda  
(Field)

San Juan  
(County or Subdivision)

New Mexico  
(State or Territory)

The elevation of the derrick floor above sea level is 6716 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

On 6-16-57, perforated the Point Lookout zone thru 5 1/2" casing with 2 holes per foot 5462'-5468', 5472'-5524', 5513'-5538' & 5580'-5592'. Sand-water fraced with 71,860 gallons of water & 60,000 lbs of sand. Injected 75 rubber balls in 5 stages during treatment. Maximum treating pressure 2200 PSI. Minimum treating pressure 900 PSI. Final pressure zero PSI. Average injection rate 42 barrels per minute.

Set bridge plug at 5456' and perforated the Anasazi & Cliffhouse zones thru 5 1/2" casing with 2 holes per foot 5105'-5120', 5134'-5146', 5150'-5160', 5180'-5195', 5220'-5228', 5270'-5274', 5288'-5300', 5328'-5348', 5372'-5392' & 5444'-5450'. Sand-water fraced with 75,500 gallons of water & 60,000 lbs. of sand. Injected 100 rubber balls in 5 stages during treatment. Maximum treating pressure 1275 PSI. Minimum treating pressure 1025 PSI. Final pressure zero PSI. Average injection rate 46.5 barrels per minute.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Blackwood & Nichols Company

Address P. O. Box 1237

Durango, Colorado

By [Signature] Delmas Lee

Title Field Superintendent