


(SUBMIT IN TRIPLICATE)

Land Office Santa Fe
Lease No. 079082
Unit Northeast Blanco

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Unit Agreement No. 1, Sec. 929



SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL		SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL		SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL		Subsequent Report of Sandfree	X

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

September 3, 1957

Well No. 50-25 is located 990 ft. from S line and 990 ft. from W line of sec. 25
NW/4 Sec. 25 31 N 8 W NMPH
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Blanco Mesaverte San Juan New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 6380 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work.)

On 7-31-57, perforated the Point Lookout zone thru 5-1/2" casing with 2 holes per foot 5576'-5596', 5600'-5610', 5618'-5638', 5654'-5664' & 5684'-5696'. Sand-water fraced with 40,194 gallons of water (including flush) and 20,000 lbs of sand. (Sand truck broke down & we were unable to use more than 20,000 lbs. of sand). Maximum treating pressure 1650 PSI. Minimum treating pressure 1250 PSI. Final pressure zero PSI. Average injection rate 51.5 barrels per minute.

Set bridge plug at 5554' and perforated the Veneee and Cliffhouse zones thru 5-1/2" casing with 2 holes per foot 5224'-5244', 5250'-5276', 5314'-5326', 5448'-5460', 5484'-5496', & 5522'-5548'. Sand-water fraced with 55,608 gallons of water (including flush) and 40,000 lbs. of sand. Injected 50 rubber balls during treatment. Maximum treating pressure 1350 PSI. Minimum treating pressure 1200 PSI. Final pressure zero PSI. Average injection rate 62.2 barrels per minute.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Blackwood & Nichols Company (Unit Operator)

Address P. O. Box 1237

Durango, Colorado

Original Signed
By Delasso Leos
by Delasso Leos

Title Field Superintendent