NEW MEXICO OIL CONSERVATION COMMISSION

Form C-122

Revised 12-1-55

MULTI-POINT BACK PRESSURE TEST FOR GAS WELLS

Pool	Blanco M	saverde	<u> </u>	Fc	rmation	Mest	verde		_County_	San Ju	AD	
Initial X Annual Special Date of Test 8-30-57												
Company Blackwood & Hichols Company Lease Northeast Blanco Unit Well No. 50-25												
Unit M Sec. 25 Twp. 31 N Rge. 8 W Purchaser El Pase Natural Gas Company												
Casing 5-1/2" Wt. 15.50 I.D. 4.90 Set							at 5744 Perf. 52241			To	6961	
Tubing 2-3/8" Wt. 4.7 I.D. 1.995 Set at 5603' Perf. 5561' To 5573'												
Gas Pay: From To L xG GL Bar.Press. 11.5												
Producing Thru: Casing Tubing X Type Well Ges Single-Bradenhead-G. G. or G.O. Dual												
Date of Completion: 8-3-57 Packer Reservoir Temp.												
OBSERVED DATA												
Test	ed Through	(Prove	(Cho	ke)	(FEET)				Type Tap	s		
	Flow Data					Tubing Da			a Casing Data			
	(Prover) (Choke)									Temp.	Duration	
No.		(Orific	ce)			°F.	Press.		psig	oF.	of Flow	
SI			, p	01g	**W		1018		1024		111 •	
1.		3/4	29	73		_	293		839		3 hrs.	
2.											T	
3.										†		
4.										 	 	
7.					~			·		 		
<u> 2• !</u>		<u> </u>								<u> </u>	<u> </u>	
]	FLOW CAL	CULATIONS	S				
	Coeffici	ent.		TPr	essure			Gravity	Compre	Rate of Flow		
No.	<u> </u>			1 '			~ .	•	,			
140.				- .		rac	COL	ractor	Factor		Q-MC-PD	
ı	(24-Hour) $\sqrt{1}$		/ hwpf	_v p _f psia		F.	t	r _g	^r pv		@ 15.025 ps1a	
1.	12.3650		304.5							3765		
3	120,7070			1200	PA3							
~-				+								
3.				-				 				
1. 2. 3. 4.				<u> </u>								
<u>5. l</u>												
					PRI	ESSURE C	ALCULATIO	ONS				
as L	iquid Hydro	carbon F	Ratio			cf/bbl	# 5 S	Speci	fic Gravi	ty Sepa	rator: Gas	
ravi	ty of Liquid	d Hydrod	carbons			dø.	Mail 1	Speci	fic Gravi	ty Flow	ving Fluid	
c			(1-e	- s)				a a Pa	1035	P_c^2 1	071	
·—			·			7	2000	**** OF		_		
						Ì	SEP 12 19	57				
	P					- { 0 11	CON. C					
No.	$P_{\mathbf{W}}$	$P_{\mathbf{t}}^2$	E ($(F_cQ)^2$	* (n	STAN C	om. I	$P_c^2 - P_w^2$	0-	, p	
MO.	_ , l	rt	F _c Q	1	(LGA)	* (P	c(2) (5) -e−s)	Ty	rc-rw	l ca	Pw Pc	
	Pt (psia)					(]	-e ⁻³)			L_{-}	w Pc	
1. 2.							The Same					
2 . [Ţ	
3• i							T					
4.				$\neg \vdash$								
3. 4. 5.				-		- 				 		
												
Abso.	lute Potent:	ial:	8582			MCFPD;	n_ •75					
COMPANY Blackwood & Nichols Company												
ADDRESS P. O. Box 1237. Darango, Colorado AGENT and TITLE Original Signed Pelasso Loos, Field Superintendent												
AGENT and TITLE Original Signed DeLasco Loos, Field Superintendent												
ALTERNA	CCED COMMITTING	by DeLass	o Loos			Lei	19950 TOO	E. Fleid	- REPORTATION	WORL .		
	ESSED	Dy Deress					.					
COMP	ANY											
						DEM	ADVC					

INSTRUCTIONS

This form is to be used for reporting multi-point back pressure tests on gas wells in the State, except those on which special orders are applicable. Three copies of this form and the back pressure curve shall be filed with the Commission at Box 871, Santa Fe.

The log log paper used for plotting the back pressure curve shall be of at least three inch cycles.

NOMENCLATURE

- Q I Actual rate of flow at end of flow period at W. H. working pressure (P_W) . MCF/da. @ 15.025 psia and 60° F.
- P_c= 72 hour wellhead shut-in casing (or tubing) pressure whichever is greater. psia
- PwI Static wellhead working pressure as determined at the end of flow period. (Casing if flowing thru tubing, tubing if flowing thru casing.) psia
- Pt Flowing wellhead pressure (tubing if flowing through tubing, casing if flowing through casing.) psia
- Pf Meter pressure, psia.
- $h_{\mbox{w}}$ Differential meter pressure, inches water.
- F_g : Gravity correction factor.
- Ft Flowing temperature correction factor.
- Fpv Supercompressability factor.
- n I Slope of back pressure curve.
- Note: If $P_{\rm W}$ cannot be taken because of manner of completion or condition of well, then $P_{\rm W}$ must be calculated by adding the pressure drop due to friction within the flow string to $P_{\rm t}$.