



(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Santa Fe

Lease No. 079045

Unit Northeast Blanco

Unit Agreement No. 1, Sec. 929

SUNDRY NOTICES AND REPORTS ON WELLS

| | | |
|--|---|---|
| NOTICE OF INTENTION TO DRILL | SUBSEQUENT REPORT OF WATER SHUT-OFF | |
| NOTICE OF INTENTION TO CHANGE PLANS | SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING | |
| NOTICE OF INTENTION TO TEST WATER SHUT-OFF | SUBSEQUENT REPORT OF ALTERING CASING | |
| NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL | SUBSEQUENT REPORT OF REPAIR REPAIR | X |
| NOTICE OF INTENTION TO SHOOT OR ACIDIZE | SUBSEQUENT REPORT OF ABANDONMENT | |
| NOTICE OF INTENTION TO PULL OR ALTER CASING | SUPPLEMENTARY WELL HISTORY | |
| NOTICE OF INTENTION TO ABANDON WELL | | |

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

September 21, 1956

Well No. 2-20 ~~Yorker~~ is located 990 ft. from S line and 1650 ft. from W line of sec. 20

34/4 Section 20
(1/4 Sec. and Sec. No.)

31N
(Twp.)

7W
(Range)

NMPM
(Meridian)

Blanco Masoverde
(Field)

San Juan
(County or Subdivision)

New Mexico
(State)

The elevation of the derrick floor above sea level is 6427 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate important proposed work)

On 8-26-56, cleaned out to original TD of 5730' and drilled 15' of new hole

On 8-27-56, ran 32 jts. 5 1/2" 14.00# & 15.50# J55 casing as liner - 1031' (with turned down collars) set at 5744' and hung at 4713' with Burns casing hanger. Cemented with 375 sacks 4 1/2 gal cement. Tested casing with 700 PSI for 30 minutes. Held OK. Cement plug back depth: 5724'. Top of cement at 4713', by temperature survey.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Blackwood & Nichols Company (Unit Operator)

Address P. O. Box 1237

Durango, Colorado

By DeLasso Lee
DeLasso Lee

Title Field Superintendent

