

	23		

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Budget Bureau No. 42-R358.4
Form Approved.

Land Office **Santa Fe**

Lease No. **078505**

Unit **E/2 Sec. 23, T-31N,**
R-9W, N.M.P.M. San Juan Cty
N.M. Communitized
NE/4, SE 078505
SE/4, N.M. 03601

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL		SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	XX	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL			

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

RECEIVED
SEP 4 1963

U. S. GEOLOGICAL SURVEY
FARMINGTON, NEW MEXICO

September 4,

1963

Well No. **7/** **Seymour** is located **1170** ft. from **N** line and **970** ft. from **E** line of sec. **23**
NE/4, NE/4, Sec. 23 **31-N** **9-W** **N.M.P.M.**
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Blanco **San Juan** **New Mexico**
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is **6436** ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Full tubing from well.

Set Bridge Plug above open hole.

Run Casing Inspection log. If casing is corroded over long intervals, run a new string of 4-1/2", OD, 10.90#, J-55 casing to T.D. If casing has holes, but balance is in good condition, the possibility of squeezing will be considered. If casing is in good condition, or after repairing, run tracer survey down bradenhead to determine where bradenhead flow is from. Also, run temperature survey while bradenhead is flowing to locate depth at which flow is from.

After locating zone flow is from, perforate below the zone and attempt to cover it with cement, or squeeze. Possibility we may perforate zone and test.

If zone produces, drill bridge plug and set Baker Model "D" packer above open hole and complete as Dual.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company **SOUTHERN UNION PRODUCTION COMPANY**

Address **P. O. Box 806**

Farmington, New Mexico

ORIGINAL SIGNED BY: **D. G. MACY**
CON. COM.
DIST. 3

By **D. G. Macy**
Title **Petroleum Engineer**