DEPUTY OIL & GAS INSPECTOR

DEC 2 2 1997

Meter Number: 70466 Location Name: RIDDLE D LS 4 Location: TN-31 RG-09 SC-22 UL-A

2 - Federal NMOCD Zone:OUTSIDE Hazard Ranking Score:00 DEGEIVED N APR 1 4 1997

VIIQ GOM. DIV. Burda

## RATIONALE FOR RISK-BASED CLOSURE OF PRODUCTION PITS LOCATED OUTSIDE OF THE VULNERABLE ZONE IN THE SAN JUAN BASIN

This production pit location was ranked according to the criteria in the New Mexico Oil Conservation Division's Unlined Surface Impoundment Closure Guidelines and received a ranking score of zero. The estimated depth to groundwater is greater than 100-feet beneath ground surface (bgs), the pit is not in a well head protection area, and there are no surface water bodies within 1,000 horizontal feet of the pit location.

The primary source, discharge to the pit has been removed. There has been no discharge to the pits for at least 4 years and the pits have been closed for at least one year.

Each pit was backfilled with clean soil and graded in a manner to divert precipitation away from the excavated area. Minimal infiltration of rainfall is expected. Any rainfall that does infiltrate the ground surface must migrate through clean backfill before reaching the residual hydrocarbons.

There is no source material at the ground surface, so direct contact of hydrocarbons with livestock and the populous is not likely.

In general, outside of the vulnerable area and alluvial valleys, bedrock material is generally encountered within 20 feet of the ground surface. Bedrock material in the San Juan Basin consists of interbedded sandstones, shales and clays. According to Freeze and Cherry, 1979, the hydraulic conductivity of the bedrock material are as follows:

Sandstone  $10^{-9}$  to  $10^{-13}$  cm/sec Shale  $10^{-12}$  to  $10^{-16}$  cm/sec Clay  $10^{-12}$  to  $10^{-15}$  cm/sec

Based on this information, the residual hydrocarbons should not migrate to groundwater.

Natural process (bioremediation) are degrading the residual hydrocarbon to carbon dioxide and water and will continue until the source is gone, therefore minimizing any impact to the environment.

Based on the above information, it is highly unlikely that any source material will impact groundwater or ever find an exposure pathway to affect human health and therefore El Paso Field Services Company (EPFS) requests closure of this pit location.




#### FIELD PIT SITE ASSESSMENT FORM

GENERAL	Meter: 70-466 Location: Riddle DLS 4  Operator #: 6203 Operator Name: Amoco P/L District: Metec  Coordinates: Letter: A Section ZZTownship: 31 Range: 9  Or Latitude Longitude  Pit Type: Dehydrator Location Drip: X Line Drip: Other:  Site Assessment Date: 9/6/94 Area: 04 Run: 53				
SITE ASSESSMENT	NMOCD Zone:  (From NMOCD  Maps)  Inside  Outside  (2)  Indian  Depth to Groundwater  Less Than 50 Feet (20 points)  Total Distance to Surface Water Body  Less Than 1000 Ft (0 points)  (1)  Yes (20 points)  (2)  NO (0 points)  (3)  Land Type:  BLM (1)  State (2)  State (2)  Fee (3)  (3)  Indian  Depth to Groundwater  Less Than 50 Feet (20 points)  (1)  50 Ft to 99 Ft (10 points)  (2)  Greater Than 100 Ft (0 points)  (3)  Wellhead Protection Area:  Is it less than 1000 ft from wells, springs, or other sources of fresh water extraction?, or; is it less than 200 ft from a private domestic water source?  (1) YES (20 points)  (2) NO (0 points)  Horizontal Distance to Surface Water Body  Less Than 200 Ft (20 points)  (1)  200 Ft to 1000 Ft (10 points)  (2)  Greater Than 1000 Ft (0 points)  (3)  Name of Surface Water Body  Lirk Canyon  (Surface Water Body: Perennial Rivers, Major Wash, Streams, Creeks, Irrigation Canals, Ditches, Lakes, Ponds)  Distance to Nearest Ephemeral Stream  (1) < 100'(Navajo Pits Only)  (2) > 100'  TOTAL HAZARD RANKING SCORE:  POINTS				
REMARKS	Remarks: Realine Book - Outside Vulnerable Zone Tope - Outside Six pits, location drip pit has liquid in it, will close				
RE	PUSHIN				

ORIGINAL	PIT	LOCATION
•		-0111101/

Original Pit: a) Degrees from North 6° Footage from Wellhead 98' b) Length: 45' Width: 39' Depth: 3'



Rem	arks	
Y/CIII	arks	

Pit is 25'x39,x3'

Completed By:

**Signature** 

Date

# FIEL PIT REMEDIATION/CLOSE..E FORM

GENERAL	Meter: 7046 Location: Riddle 015 #4  Coordinates: Letter: A Section 22 Township: 31 Range: 9  Or Latitude Longitude  Date Started: 10/3/94 Run: 04 53
FIELD OBSERVATIONS	Sample Number(s): KO 30/  Sample Depth: 6 Feet  Final PID Reading 777 ppn PID Reading Depth 6 Feet  Yes No  Groundwater Encountered
CLOSURE	Remediation Method:  Excavation
REMARKS	Remarks: Excample test the to6, Hit Sandstone, Took  P.D. Stample, Closed Dit.  Signature of Specialist: My Man.



## FIELD SERVICES LABORATORY ANALYTICAL REPORT

#### PIT CLOSURE PROJECT - Soil Samples Outside the GWV Zone

#### SAMPLE IDENTIFICATION

_	Field I	D		Lab ID		
SAMPLE NUMBER:	SAMPLE NUMBER: WD 30.1		9463	506.		
MTR CODE   SITE NAME:			N/A			
SAMPLE DATE   TIME (Hrs):	10-3-0	1	1025			
SAMPLED BY:		N/A	Α			
DATE OF TPH EXT.   ANAL.:	10-6-94					
DATE OF BTEX EXT.   ANAL.:	NIA		N	М		
TYPE   DESCRIPTION:			Frey brown sand & clay			
·			U []		1	
REMARKS:			1			
MEINANICO						
	F	RESULTS				
DADAMETER	RESULT	UNITS	QUALIFIERS			
PARAMETER	RESULI	UNITS	DF	Q	M(g)	V(ml)
TPH (418.1)	15300	MG/KG			0.17	28
HEADSPACE PID	777	PPM				
PERCENT SOLIDS	81.8	%				
	•	- TPH is by EPA Method	i 418.1			
arrative:						
F = Dilution Factor Used			-			
$\searrow \bigcirc$				Shalad		

Test Method for Oil and Grease and Fetroleum Hydrocarbons in Water and Soil Perkin-Elmer Model 1600 FT-IR 

94/10/06 14:00

Tample identification 146304

Thitial mean of eample, g

Volume of cample after extraction. Al 18 000

Tatrolaum sydrocardonal pom .5008.175 Net kosprbacca of bechocarburs (271) cm-19 ...49

