Form C-122

MULTI-POINT BACK PRESSURE TEST FOR GAS WELLS

Revised 12-1-55

Pool	Blanc	<u> </u>		F	ormation	Me	Werde	 	County	San	Juan	
Initi	al	<u> </u>	Annu	al		Spec	cial	·	Date of	Test	10-4-57	
	ny Pacifi											
	# 7-5/8											
Casin	lg 5-2 h	/t	I	.D	Se	t at	6030 _{Pe}	rf	5998	То	5478	
Tubin	g 1-1/4 W	/t	I	•D•	Se	t at	5998 Pe	rf		То		
Gas P	ay: From_		_To		L		_{cG} .65 (e	st)_GL_		Bar.Pr	ess	
Produ	cing Thru:	Cas	sing	XX	Tu	bing		Type We	ellsin	gle		
Date	of Complet	ion:_			Packe:	r	Sin	gle-Brade Reserve	enhead-G. oir Temp	G. or (G.O. Dual	
							ED DATA					
Teste	d Through	(P ?	619 (Choke)	(Meter)	Shar	in 7 de	a.	Туре Тар	s		
			low Da					Data		ata		
No	(Prover) (Line)	(Cho	ke)	Press.	Diff.	Temp.	Press.	Temp.	Press.	Temp.		
	Size	Si	ze	psig	h _w	o _F .	psig	o _F .	psig	[⊃] F•	of Flow Hr.	
SI							1065		1113		shut in	
1. 2.		3/4"	T.C.	152		68	238		152		3 heurs	
3.		 							<u> </u>		 	
4.									 		 	
5.												
					T	TAD DATE	CIT AMTON	.				
	Coeffici	ent.		Pr			CULATION		Compres		Rate of Flow	
No.						Fac	tor	Factor	Factor	r	Q-MCFPD	
			√ h _w r	Pf			t	F _g	Fpv			
1. 2.	12.365				164	•99	31	.9608		1.915	1974	
3.												
3. 4. 5.												
5.												
T.		,	.				ALCU ATIO	- '	•	_		
	quid Hydro y of Liquid					cf/bbl. deg.			fic Gravit fic Gravit			
C		u 11.j u1		L-e ^{-s})		ucg•		P _c			1239	
							•	C	,	- (
No.	Expx(psia)	Pt2	Fo	Q	$(F_cQ)^2$	(F.	c ^{Q)²} -e ^{-s})	P _w 2	$P_c^2 - P_w^2$	Ca	Pw Pc	
1. 2.	250							62.5	1176	 	V 1.0536	
2.												
2•										 	_	
3. 4. 5.			_							 		
Absolu	ite Potent	ial:_	8	1053		MCFPD;	n •	75/ 1.04	0	J	-, -,- <u>-</u>	
	Y Pacific						ri oc					
	and TITLE		. 6. 1			Test I				···-		
WITNES	-	W.	<u>- </u>		# # # # #	<u>. 4454 W</u>	- Prince					
COMPAN											a sec	
						REM	ARKS			10%	C	

INSTRUCTIONS

This form is to be used for reporting multi-point back pressure tests on gas wells in the State, except those on which special orders are applicable. Three copies of this form and the back pressure curve shall be filed with the Commission at Box 871, Santa Fe.

The log log paper used for plotting the back pressure curve shall be of at least three inch cycles.

NOMENCLATURE

- Q = Actual rate of flow at end of flow period at W. H. working pressure (P_w). MCF/da. @ 15.025 psia and 60° F.
- P_c 72 hour wellhead shut-in casing (or tubing) pressure whichever is greater. psia
- P_{w} Static wellhead working pressure as determined at the end of flow period. (Casing if flowing thru tubing, tubing if flowing thru casing.) psia
- Pt Flowing wellhead pressure (tubing if flowing through tubing, casing if flowing through casing.) psia
- P_{f} Meter pressure, psia.
- hw Differential meter pressure, inches water.
- $F_g = Gravity$ correction factor.
- Ft Flowing temperature correction factor.
- Fpv Supercompressability factor.
- n I Slope of back pressure curve.

Note: If $P_{\rm W}$ cannot be taken because of manner of completion or condition of well, then $P_{\rm W}$ must be calculated by adding the pressure drop due to friction within the flow string to $P_{\rm t}$.

OIL CONSERVA	TIÓN COMMI	ŜŜIÕN						
AZTEC DISTRICT OFFICE								
No. Copies Received 3								
OBIRISETION								
	ON CENTRAL							
* Operator	100							
Santa Fo	. 7							
Proration Office		1						
State Land Office								
USGS		1						
Transporter								
File		-						
•								