



SUBMIT IN TRIPLICATE)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Land Office Santa Fe  
Lease No. U.S. 03402  
Unit 30-9  
# 14-03-003-446

## SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

July 19, 1956, 19

Well No. 14-13 is located 1190 ft. from S line and 800 ft. from W line of sec. 13

14-13 (Sec. and Sec. No.) 31-8 (Twp.) 24 (Range) 1-2-13 (Meridian)  
San Juan (County or Subdivision) New Mexico (State or Territory)

The elevation of the derrick floor above sea level is 6145.6 ft.

### DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Moved on completion rig, tested casing w/1500' for 30 minutes, tested  
OIL. Total depth 3030', part 5700-58', 5700-56', 5700-54', 5700-52', 5700-50',  
5700-48', 5700-46', 5700-44', w/ 2 shots/ft. from 121 w/12, 150 gals water only,  
NO 1500', avg. 1250', max. 1400', final 1250', to vac. IN 55.6 RPM. Perf. 5600-  
54', 5600-52', 5600-50', 5600-48', w/ 2 bullets/ft. set 12' at 5700' and fr-s  
w/12, 150 gals water only, NO 1500', avg. 1700', max 1775' final 1775', to  
vac. IN 68 RPM. Perf. 5700-544', 5700-52', 5700-50', 5700-48', 5700-46', 5700-44',  
5700-42', w/ 2 shots/ft. set 12' at 5800', from 121 w/12, 150 gals water only,  
NO 1500', avg. 1750', max 1775', final 1775', to vac. IN 62.5 RPM. Perf. 5800-  
64', 5800-62', 5800-60', 5800-58', w/ 2 shots/ft. part 5900-57', 5900-55',  
5900-53', w/ 3 shots/ft. set 12' at 5975', fr-s Cliff House w/12, 150 gals water  
only NO 1500', avg. 1775', max 1800', final 1800', to vac. IN 62.5 RPM, cleaned  
out to total depth, run tubing and released rig 10:30 PM 7-9-56.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Pacific Northwest Pipeline Corp.

Address 1051 K. Broadway

Farmington, New Mexico

By Original signed by T. A. Dugan

Title District Engineer

RECEIVED

APR 24 1968  
U. S. GEOLOGICAL SURVEY  
WASHINGTON, D. C. 20540