3-MOOS Astes 1-Mill Octler 1-W. R. Jehnston 1-Gliver Forler' 1-Wayne Smith 1-File

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-122

MULTI-POINT BACK PRESSURE TEST FOR GAS WELLS

Revised 12-1-55

Poo	l <u>Elanco M</u>	iss Year	de	F	ormation_	Mess '	Verde		_County	San Ji	ian	
Initial Annual							·	Date of Test 6.30.57			<u>, </u>	
om	pany Pacific	Morthe	est_l	Pipeli	ne Gerne i	chica	See Jus	n 39-	g Wel	l No.	1-15	
	t 7-/5/8 Se	2.3				1. 1. 1		_				
as:	7-/5/8 ing 5 2 Wt		I.	. D .	Set	at 🥦	Pe	rf. 5	982	To 54	70	
	ing 1-1/4 Wt											
	Pay: From_				-							
coc	ducing Thru:	Casi	ng	x	Tub	ing		Type We	11 Si n	gle		
ıt.	e of Completi	lon:			Packer	•	Sin	gle-Brade Reservo	nhead-G. ir Temp.	G. or (3.0. Dua	L
st	ted Through	(Prove	r) (0	Choke)	(Meter)	OBSERV	ED DATA		Туре Тар	s	414	904
	(30.00.00		ow Da		. Diff.	Town	Tubing	Data Temp.	Casing D	ata Torro	D.,,	est i or
۰.	(Hite)	40000				•		•		oF.	0:	Flov
	*629 0	Size	9	psig	h _w	°F.	psig	F.	psig	F.	Silvents 7	
		V	T	239		670	272				3 Era	
	Coefficient Pr				B		Compress. Factor		Rate of Flow Q-MCFPD @ 15.025 psis			
	14,1605				251	.99	33	.9608	1.08	3	3470	
$\frac{1}{1}$												
v.	Liquid Hydroc ity of Liquid		carbo			SSURE C.cf/bbl.deg.		Speci Speci	fic Gravi fic Gravi	ty Flow		
- [P _w	$P_{\mathbf{t}}^{2}$	F		1/+cQ)2	(F)	c ^{Q)2} -e ^{-s})	P _w 2	$P_c^2 - P_w^2$	Ca I	al.	. c
'-			1,11		3K) - 157			86656	Shophi		1.0	959_
	284					3				1		
	264				<u> </u>	: 1	1					
) Som	olute Potenti		371	Z Isolika		MCFPD;	n75/_	1.0711	Fr.	TEIN		
OMI ODI BEI	olute Pocenti	lesthere t Tene				MCFPD;	n75/	1.0711	ON COL	TEN CON	(b)	

INSTRUCTIONS

This form is to be used for reporting multi-point back pressure tests on gas wells in the State, except those on which special orders are applicable. Three copies of this form and the back pressure curve shall be filed with the Commission at Box 871, Santa Fe.

The log log paper used for plotting the back pressure curve shall be of at least three inch cycles.

NOMENCLATURE

- Q I Actual rate of flow at end of flow period at W. H. working pressure (P_w) . MCF/da. @ 15.025 psia and 60° F.
- P_C= 72 hour wellhead shut-in casing (or tubing) pressure whichever is greater. psia
- PwT Static wellhead working pressure as determined at the end of flow period. (Casing if flowing thru tubing, tubing if flowing thru casing.) psia
- P_t Flowing wellhead pressure (tubing if flowing through tubing, casing if flowing through casing.) psia
- Pf Meter pressure, psia.
- $h_{\mbox{\scriptsize W}}\mbox{\footnotesize I}$ Differential meter pressure, inches water.
- FgI Gravity correction factor.
- F_t Flowing temperature correction factor.
- F_{DV} Supercompressability factor.
- n I Slope of back pressure curve.

Note: If $P_{\mathbf{W}}$ cannot be taken because of manner of completion or condition of well, then $P_{\mathbf{W}}$ must be calculated by adding the pressure drop due

to friction within the flow string to Pt ,

OIL CONSERVAT	ION COMMIS	SION							
AZTEC DISTRICT OFFICE									
No. Copies Received 3									
DISTRIBUTION									
	NO. FURNISHED								
Operator									
Santa Fe									
Proration Office									
State Land Office									
U. S. G. S.		•							
Transporter									
File	/								