

MULTI-POINT BACK PRESSURE TEST FOR GAS WELLS

Pool Blanco Mesaverde Formation Mesaverde County San Juan County
Initial X Annual _____ Special _____ Date of Test August 5, 1958
Company Southern Union Gas Company Lease Quinn Well No. 7
Unit A Sec. 17 Twp. 31 Rge. 8 Purchaser Southern Union Gas Co.
Casing 7-5/8 Wt. 26.40 I.D. 4.950 Set at 3560 KB Perf. 5316 To 5516
Tubing 2-3/8 Wt. 4.7 I.D. 1.995 Set at 6025 Perf. 6010 To 6025
Gas Pay: From 5316 To 5516 L 6010 xG 0.67 -GL 1026 Bar.Press. 12.0
Producing Thru: Casing _____ Tubing X Type Well Single-Gas
Single-Bradenhead-G. G. or G.O. Dual
Date of Completion: July 13, 1958 Packer _____ Reservoir Temp. _____

OBSERVED DATA

Tested Through (Bottom) (Choke) (Surface) Type Taps _____

No.	Flow Data					Tubing Data		Casing Data		Duration of Flow Hr.
	(Prover) (Line) Size	(Choke) (Orifice) Size	Press. psig	Diff. h _w	Temp. °F.	Press. psig	Temp. °F.	Press. psig	Temp. °F.	
SI						1085		1092		22 days
1.		3/4"	255		70°	255	70°	834	70°	3 hours
2.										
3.										
4.										
5.										

FLOW CALCULATIONS

No.	Coefficient (24-Hour)	$\sqrt{h_w P_f}$	Pressure psia	Flow Temp. Factor F _t	Gravity Factor F _g	Compress. Factor F _{pv}	Rate of Flow Q-MCFPD @ 15.025 psia
1.			267	.9985	.9163	1.028	3.181
2.							
3.							
4.							
5.							

PRESSURE CALCULATIONS

Gas Liquid Hydrocarbon Ratio _____ cf/bbl.
Gravity of Liquid Hydrocarbons _____ deg.
P_c _____ (1-e^{-s})
Specific Gravity Separator Gas _____
Specific Gravity Flowing Fluid _____
P_c 1104 P_c 1218.8
P_w 846 P_w 715.7

No.	P _w P _t (psia)	P _t ²	F _c Q	(F _c Q) ²	(F _c Q) ² (1-e ^{-s})	P _w ²	P _c ² -P _w ²	Cal. P _w	P _w P _c
1.						715.7	503.1		.766
2.									
3.									
4.									
5.									

Absolute Potential: 6.176 MCFPD; n .75
COMPANY Southern Union Gas Company
ADDRESS P. O. Box 815 - Farmington, New Mexico
AGENT and TITLE G. L. Hoffman
WITNESSED _____
COMPANY _____

REMARKS



INSTRUCTIONS

This form is to be used for reporting multi-point back pressure tests on gas wells in the State, except those on which special orders are applicable. Three copies of this form and the back pressure curve shall be filed with the Commission at Box 871, Santa Fe.

The log log paper used for plotting the back pressure curve shall be of at least three inch cycles.

NOMENCLATURE

Q = Actual rate of flow at end of flow period at W. H. working pressure (P_w).
MCF/da. @ 15.025 psia and 60° F.

P_c = 72 hour wellhead shut-in casing (or tubing) pressure whichever is greater.
psia

P_w = Static wellhead working pressure as determined at the end of flow period.
(Casing if flowing thru tubing, tubing if flowing thru casing.) psia

P_t = Flowing wellhead pressure (tubing if flowing through tubing, casing if
flowing through casing.) psia

P_f = Meter pressure, psia.

h_w = Differential meter pressure, inches water.

F_g = Gravity correction factor.

F_t = Flowing temperature correction factor.

F_{pv} = Supercompressability factor.

n = Slope of back pressure curve.

Note: If P_w cannot be taken because of manner of completion or condition of well, then P_w must be calculated by adding the pressure drop due to friction within the flow string to P_t .

OIL CONSERVATION COMMISSION		
AZTEC DISTRICT OFFICE		
No. Copies Received <u>3</u>		
DISTRIBUTION		
	NO. FURNISHED	
Operator		
Santa Fe	1	
Proration Office		
State Land Office		
U. S. G. S.	1	
Transporter		
File	1	1