

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-015
Expires: March 31, 1993

SUNDY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir,
Use "APPLICATION FOR PERMIT" for such proposals

1. ☐ Oil Well ☒ Gas Well ☐ Other

2. Phillips Petroleum Company

3. 5525 Hwy. 64, NBU 3004, Farmington, NM 87401 (505) 599-3454

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1650' FNL & 790' FEL
Section 8, T-31-N, R-7-W

5. Lease Designation and Serial Number

SF-078996

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

San Juan 32-7 Unit

8. Well Name and No.

San Juan 32-7 Unit # 5

9. API Well No.

30-045-10934

10. Field and Pool, or Exploratory Area

Blanco Mesaverde

11. County or Parish, State

San Juan, NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☒ Notice of Intent

☐ Subsequent Report

☐ Final Abandonment Notice

TYPE OF ACTION

☒ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☐ Other

☒ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut-Off

☐ Conversion to Injection

☐ Dispose Water

(Note Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimate date of starting any proposed work. If well is directionally drilled, give subsurface locations and true vertical depths for all markers and zones pertinent to this work.)

Plans were submitted to T/A the above mentioned well, but a leak was found while doing the casing integrity test.

The 1-1/4" and 1" tubing was fished down to 3843' and verbal approval was obtained from Steve Mason (BLM) on Oct. 3, 1994 to set a cement retainer at 3810' and squeeze 110 sxs Cl B cement below and spot 10 sxs Cl B cement on top of retainer.

Verbal approval was obtained Oct. 4, 1994 from Steve Mason for the following procedure.

Perf. 7" casing @ 3478'. Set cement retainer @ 3428'. Perf. 7" casing @ 2988'. Pump 85 sxs Cl B cement below retainer and spot 104 sxs Cl B above retainer to isolate Pictured Cliffs & Fruitland Coal. Spot balanced plug (50 sxs Cl B cement) from 2449' - 2245' to isolate Ojo Alamo. Perf 7" casing @ 952'. Set cement retainer @ 902'. Pump 45 sxs Cl B below retainer and spot 10 sxs Cl B above retainer to isolate Nacimiento. Perf 7" casing @ 223'. Circ. 123 sxs to surface inside & outside 7" casing. Cut off casing, cap, and place abandonment marker.

14. I hereby certify that the foregoing is true and correct.

Signature Ed Hasely

Ed Hasely

Title Environmental/Regulatory Engineer

Date 10-4-94

(This space for Federal or State office use)

Approved by

Title

Date

Conditions of approval, if any:

APPROVED

OCT 04 1994

DISTRICT MANAGER

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make any statement or representation of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.