



(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYLand Office Santa Fe
Lease No. 078788
Unit Northeast Blanco
Unit Agrmt. No. 1, Sec. 929

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....
NOTICE OF INTENTION TO ABANDON WELL.....	Subsequent Report of Sand-Water Frac X

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

June 2, 1961

Well No. 60-7 is located 1090 ft. from N line and 1250 ft. from E line
NE/4 Section 7 31N 6W NMPM
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Blanco Mesaverde San Juan New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 6380 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

On 5/29/61, perforated the Point Lookout Formation through 5 1/2" casing with 2 holes per foot 5626' - 5662', 5678' - 5684', 5696' - 5712', 5719' - 5735' & 5770' - 5786'. Sand-water fraced 40,200 gallons of water (including flush) and 25,000 lbs. of sand. Maximum treating pressure 1300 PSI. Minimum treating pressure 1200 PSI. Final pressure zero PSI. Average injection rate 46 BPM.

Set Baker magnesium bridge plug at 5600' and perforated the Menefee & Cliffhouse Formations through 5 1/2" casing with 2 holes per foot 5538' - 5575', 5457' - 5479', 5504' - 5522', 5532' - 5550' & 5557' - 5575'. Sand-water fraced with 40,320 gallons of water (including flush) and 25,000 lbs. of sand. Injected 30 rubber sealers during treatment. Maximum treating pressure 1600 PSI. Minimum treating pressure 1200 PSI. Final pressure 500 PSI. Average injection rate 44 BPM.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Blackwood & Nichols Company (Unit Operator)Address P. O. Box 1237Durango, ColoradoBy Original Signed DeLasso Loos
by DeLasso LoosTitle Field Superintendent