00100

District I
F O. Box 1980, Hobbs, NM
District II
P.O. Drawer DD, Artesia, NM 88211
District III
Rio Brazos Rd, Aztec, NM 87410

State of New Mexico Energy, Minerals and Natural Resources Department

P.O. Box 2088

P.O. Box 2088

Santa Fe, New Mexico 87504-2088

MAY 2001
PECALED
CALCALE
DATE

SUBMIT 1 COPY TO

DISTRICT OFFICE

APPROPRIATE

PIT REMEDIATION AND CLOSURE REPOR

Operator:	Amoco Production Company	Telephone: (505) - 326-9200
Address:	200 Amoco Court, Farmingto	n, New Mexico 87401
Well Name Location: Unit ASPON Pit Type: Sepa	rator / Dehydrator	ec (4 T3DA R9W County SAN JUAN) Other Other
Pit Location: Attach diagram)	Reference: wellhead X	n 18', width Zl', depth 4' , other 81' Se: 79 Degrees East North West South _/
Depth To Groun (Vertical distance contaminants to s high water elevat ground water)	e from easonal	Less than 50 feet (20 points) 50 feet to 99 feet (10 points) Greater than 100 feet (0 Points)
Wellhead Protection Area: (Less than 200 feet from a private domestic water source, or; less than 1000 feet from all other water sources)		Yes (20 points) No (0 points) <u>o</u>
Distance To Surface To	nce to perennial ers, streams, creeks,	Less than 200 feet (20 points) 200 feet to 1000 feet (10 points) Greater than 1000 feet (0 points)
		RANKING SCORE (TOTAL POINTS):

BOTSO ABAN. SEP. PIT Date Remediation Started: Date Completed: 8/9/00 Remediation Method: Excavation \times Approx. cubic yards 50 (Check all appropriate Landfarmed ___ Insitu Bioremediation ___ sections) Other CompositeD Remediation Location: Onsite Offsite ✓ NHE GC B #1€ (E-7-29-9) (ie. landfarmed onsite, TRANSPORTED TO CROUCH MECA 3/01. name and location of offsite facility) General Description Of Remedial Action: Excavation mostly BEDIDEK Ground Water Encountered: No ____ Yes ___ Depth____ Sample location see Attached Documents Final Pit: Closure Sampling: (if multiple samples, attach sample results Sample depth 5' (PIT BOTTOM) and diagram of sample locations and depths) Sample date 8/9/05 Sample time 1406 Sample Results Benzene(ppm) Total BTEX(ppm) ____ Field headspace(ppm) 141 TPH NA Ground Water Sample: Yes ___ No ✓ (If yes, attach sample results) I HEREBY CERTIFY THAT THE INFORMATION ABOVE IS TRUE AND COMPLETE TO THE BEST OF MY KNOWLEDGE AND BELIEF

DATE 8/9/00

SIGNATURE BAS haw

PRINTED NAME AND TITLE Buddy D. Shaw Environmental Coordinate

	J-73/10			
CE1C111	BLAGG ENGINEERING, INC. DX 87, BLOOMFIELD, NM 87413 (505) 632-1199	C.D.C. ND:		
FIELD REPORT: (CLOSURE VERIFICATION	PAGE No: _/_ of _/_		
QUAD/UNIT: M SEC: 14 TWP: 30N RNG: 9W PM: NM CNTY: 57 ST: NM				
QTR/FOOTAGE: 855'5 1060'W	ENVIRONMENTAL SPECIALIST: NV			
DISPOSAL FACILITY: MIE GE	21 FT. x 4 FT. DEEP. CUBIC 31E(E-7-29-9) REMEDIATION METHO	DD: COMPOSTED		
LAND USE: RANGE LEASE: SF 80004 FORMATION: PC				
FIELD NOTES & REMARKS: PIT LOCATED APPROXIMATELY 81 FT. 579W FROM WELLHEAD. DEPTH TO GROUNDWATER: 2120' NEAREST WATER SOURCE: >1000' NEAREST SURFACE WATER: >1000'				
NMOCD RANKING SCORE: O NMOCD TPH CLOSURE STD: 5000 PPM CHECK ONE: PIT ABANDONED				
SOIL AND EXCAVATION DESCRIPTION:				
25. 20.00 to 10.00 to	E MOSTLY BEDROCK (SANDSTONE) COUR	FIBERGLASS TANK INSTALLED		
ORANGE TO DK. GRAY (O	um sample) very hard e pit bettom ,	" STAINING PRIERUEN		
WITHIN TANDSTONE UN W TAMPLE FROM BEORDCA	EST SIDEWALL & APPROX. 3 FT. BE THEREFORE NO TON AMOUTS IS WAS	CONDUCTED		
	,			
RISK ASSESSED				
MOSTLY BEDROCK	FIELD 4101 CALCULATIONS			
TIME	FIELD 418.1 CALCULATIONS SAMPLE I.D. LAB NO: WEIGHT (g) mL. FREON D	ILUTION READING CALC. ppm		
SCALE /400				
O FT				
PIT PERIMETER		PROFILE		
	OVM RESULTS A	, A'		
18 1	SAMPLE FIELD HEADSPACE PID (ppm)	21)		
<u> </u>	2 @			
T	/ 13 @ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \			
	4 @	777		
, 5 ,	4 و ا	Prock 775'		
€ 21 E	4 و ا	Prock 775'		
	4 و ا	Prock 775'		
e zi E	LAB SAMPLES	PROCK 775'		
e zi E	5 @ SE(PROCK 775'		
E P P P P P P P P P P P P P P P P P P P	LAB SAMPLES	PROCK 775'		
E P P P P P P P P P P P P P P P P P P P	LAB SAMPLES	PROCK 755		

Well Name:
Well Site location:
Pit Type:
Producing Formation:
Pit Category:
Horizontal Distance to Surface Water:
Vicinity Groundwater Depth:

Florance #58
Unit M, Sec. 14, T30N, R9W
Abandoned Separator Pit
Pictured Cliffs
Non Vulnerable
> 1000 ft.
> 100 ft.

RISK ASSESSMENT (non-vulnerable area)

Pit remediation activities were terminated when backhoe encountered competent sandstone at 4 feet below grade.

No past or future threat to surface water or groundwater is likely based on the following considerations:

- 1. Groundwater levels located on or close to the well pad are estimated to be at a much greater depth below shallow sandstone bedrock.
- 2. Topographic information does not indicate off site lateral fluid migration near the earthen pit.
- 3. Daily discharge into the earthen pit has been terminated (pit abandoned). Prior discharge into the pit is believed to be under 5 barrels per day.
- 4. Well site located within the <u>non-vulnerable area</u> and is approximately 1.58 miles south of the nearest vulnerable area boundary (Crow Canyon wash).

(Refer to <u>Turley Quadrangle</u>, <u>New Mexico</u> - <u>San Juan County</u>, <u>7.5 Minute Series</u> (<u>Topographic</u>), <u>Provisional edition</u>, <u>1985</u>, (<u>vulnerable area boundary developed by Mr. William C. Olson</u>, <u>Hydrogeologist</u>, <u>Environmental Bureau</u>, <u>New Mexico Oil Conservation Division</u>).

Based upon the information given, we conclude that the subsurface vertical impact from the earthen pit is very limited and that the sandstone bottom creates enough of a impermeable barrier as to subdue impact to groundwater below it (please refer to BP AMOCO's (formerly Amoco Production Company) report "Post Excavation Pit Closure Investigation Summary, July, 1995", with cover letter dated November 30, 1995). BP AMOCO therefore request pit closure approval on this location.