COD XERO

XERO

S Addiction

5 USCS 1 Navajo Tribe 1 Chevron 1 File

Form 9-331 (May 1963)	UNITED STATES SUBMIT IN TRIPLICATE*			Budget Bu	Form approved. Budget Bureau No. 42-F:1424. 5. LEASE DESIGNATION AND SERIAL NO. 14-20-C603-8492		
	DEPARTMENT OF THE INTERIOR verse side)						5. LEASE DESIGNATI
GEOLOGICAL SURVEY					6. IF INDIAN, ALLOTTUE OR TRIBE NAME		
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)					- Mavajo		
OIL GAS	X OTHUR				7. UNIT AGREEMENT	NAME	
WELL WELL OTHUR 2. NAME OF OPERATOR					S. FARM OR LEASE	S. FARM OR LEASE NAME	
Thomas A. Dugan					Shiprock		
3. ADDRESS OF OPERATOR Box 234, Farmington, N. M. 87401					9. WELL NO. 5		
 LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 						10. Field and Poot, or Wildcat Wildcat	
1650' fnl 1870' fel					11. SEC., T., 2., M., SURVEY OR A	11. SEC., T., E., M., ON BLK. AND SURVEY OR ARIA	
					14-30N-18W	17-30N-TSM NARC	
14. PERMIT NO.		15. ELEVATIONS (Sho		r, GR, etc.,	San Juan	New Mexico	
16.	Check A	opropriate Box To	Indicate Nat	ture of Notice, Report, o	r Other Data		
	NOTICE OF INTER	•			SEQUENT REPORT OF:		
TEST WATER SHUT-	OFF	PULL OR ALTER CASING	, [WATER SHUT-OFF	BEPAIRI	NG WELL	
FRACTURE TREAT		MULTIPLE COMPLETE		PRACTURE TREATMENT	ALTERIN	G CASING	
SHOOT OR ACIDIZE		ABANCON*		SECOTING OR ACIDIZING	ABANDO!	NMENT*	
REPAIR WELL		CHANGE PLANS		(Other)	ults of multiple complet	ion on Well	
(Other)				Completion or Reco	empletion Report and Lo	g Iorm.)	
nent to this work.)	. •			eable tool rig - s		-	
1-15-67	Drilling in boulders at 20°					OFFFIVE	
1-16-67	Drilling in boulders at 25'				. (New York	
1-17-67	Drilled to 63', ran 2 jts. 5 1/2" surface casing. Cemented w/5 sx. Oll CC						
2-28-67	Move in Crane Drilling Co. Rotary rig, drill 4 3/4" hole w/air to 230'.						
3-1-67	Drilled 4 3/4" hole w/air to 387', well making 1200 MCFPD from Gallup 378 to 387. Pan 15 jts. 2 7/8" 0.D. 5.9# blk. T & C line pipe. T.E. 388.78 set at 387' ground level with 12' perf. subs on bottom and larkin packer set at 378. Cemented tubing in hole w/10 sx neat. Blowing well.						
18. I hereby certify th	n+ the foreteing	is true and correct					
SIGNED	1. Dec	<u> </u>	TITLE	Operator	DATE	3/21/67	
(This space for Fe	deral or State o	ffice use)	TITLE		RECE	IVED	
CONDITIONS CD	APPROTAL, IF	ANY:			MAR 2	1 12.27	

*See Instructions on Reverse Side

U. S. GEOLOGICAL SURVEY