

Indian Agency

Navajo Tribal

Lease No. 14-20-603-2028

Unit

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

U. S. GEOLOGICAL SURVEY

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE Casing	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	X
NOTICE OF INTENTION TO ABANDON WELL		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Navajo Tribal 130-15

Well No. 1 is located 660 ft. from {S} line and 660 ft. from {E} line of sec. 15

SE $\frac{1}{4}$ of SE $\frac{1}{4}$, Sec 15 30N 17W 10PM
($\frac{1}{4}$ Sec. and Sec. No.) (Twp.) (Range) (Meridian)

Undesignated San Juan New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 5240 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Drilled to total depth of 7927'. 5-25-64, conducted D.S.T. No. 4 7796-7922' (Paradox) Tool open with very weak blo dying in 12 minutes. Took ISIP. Re-opened tool with no blow. Recovered 15' drilling mud, no show. IFP 132, ISIP 1074, FFP 132, FSIP 394, IAFH 4278. BHT 142°. Ran drill pipe and conditioned hole.

Following is the plugging detail:

50 sx cement plug 7750' to 7922'	50 sx cement plug 2525' to 2625'
40 sx cement plug 7100' to 7200'	100 sx cement plug 1300' to 1525'
50 sx cement plug 5900' to 6050'	10 sx cement plug At Surface
75 sx cement plug 4200' to 4350'	

WOC on top plug @ 4:00 A.M. WOC 6 hrs. Tagged top plug with 10,000# at 1250'. Layed down D.P. spotted 10 sx cement in top of surface pipe. Capped well, released rig 12:00 noon 5-26-64. Install dry hole marker and clear location per USGS requirements

Understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company STANDARD OIL COMPANY OF TEXAS, A Division of California Oil Company

Address 3610 Avenue S

Snyder, Texas

By R. E. Rigsby R. E. Rigsby

Title Lead Drilling Engineer