

Section 15

(SUBMIT IN TRIPLICATE)

Budget Bureau No. 42-11-389.a.
Approval expires 12-31-65.Indian Agency Navajo TribalUNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Allottee

Lease No. 14-20-603-2023

660' FSL & 660' FEL

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	<input type="checkbox"/>
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	<input type="checkbox"/>
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	<input type="checkbox"/>
NOTICE OF INTENTION TO REDRILL OR REPAIR WELL	SUBSEQUENT REPORT OF REDRILLING OR REPAIR	<input type="checkbox"/>
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	<input type="checkbox"/>
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	<input checked="" type="checkbox"/>
NOTICE OF INTENTION TO ABANDON WELL		<input checked="" type="checkbox"/>

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

May 26, 1964

Navajo Tribal 130-15

Well No. 1 is located 660 ft. from S line and 660 ft. from E line of sec. 15SE¹ of SE¹, Sec. 15
(1/4 Sec. and Sec. No.)30N 17W
(Twp.) (Range)NMPM
(Meridian)Undesignated
(Field)San Juan
(County or Subdivision)New Mexico
(State or Territory)The elevation of the derrick floor above sea level is 5240 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Drilled to total depth of 7000'. 5-25-64, conducted D.S.T. No. 4. 7796-7922' (Paradox)
Tool open with very weak blow dying in 12 minutes. Took ISIP. Re-opened tool with
no blow. Recovered 15' drilling mud, no show. IFT 132, ISIP 10 7/4, FTF 132, FSIP 394,
I&FH 4278. BHT 172°. Ran drill pipe and conditioned hole. The Standard Oil Company
of Texas, A Division of California Oil Company hereby gives Notice of Intention to
plug and abandon subject well by spotting cement plugs as follows:

- 50 sx cement plug T.D. - 7750'
- 40 sx cement plug 7200 - 7100'
- 50 sx cement plug 6050-5900'
- 75 sx cement plug 4350-4200'
- 50 sx cement plug 2625-2525'
- 100 sx cement plug 1525-1300'
- 10 sx cement plug at surface.

-- Install dry hole marker and clear location per
U.S.G.S. requirements.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Standard Oil Company of Texas, A Division of California Oil CompanyAddress Drawer "S"Monahans, TexasBy J. L. RowlandTitle District Engineer