

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other

2. NAME OF OPERATOR

Southland Royalty Company

3. ADDRESS OF OPERATOR

P.O. Drawer 570, Farmington, New Mexico

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: *1600' FSL & 1150' FWL*

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON* ☒

(other)

SUBSEQUENT REPORT OF:

☐

☐

☐

☐

☐

☐

☐

☐

☐

5. LEASE

SF-077922

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Hudson, J.

9. WELL NO.

4

10. FIELD OR WILDCAT NAME

Fulcher Kutz Pictured Cliffs

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Section 35, T30N, R12W

12. COUNTY OR PARISH

San Juan

13. STATE

New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

5858' GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

SOUTHLAND ROYALTY COMPANY hereby proposes to Plug and Abandon this well as follows:

- 1. Spot cement plug from 2145'-1900'.*
- 2. Spot plug from 1725'-1625' to cover Fruitland top at 1625'.*
- 3. Perforate at 590' and squeeze 100' + 50% behind casing and spot plug 590'-490' to cover Ojo Alamo top at 540'.*
- 4. Perforate casing at 140' and spot cement plug inside and outside casing to surface.*

Changes per telephone conversation with Richard Bell on 6-4-82 with Terry Hobbs.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED *R. E. Fiddle* TITLE *Dist. Engineer* DATE *June 4, 1982*

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL

APPROVED

James F. Sims
JUN 11 1982

For JAMES F. SIMS
DISTRICT ENGINEER

TITLE _____

DATE _____

*See Instructions on Reverse Side

NMOCC

