
DEPUTYOU & GAS INSPECTOR

**DEC** 2211997

Meter Number: 75994
Location Name: DELHI STATE COM #1X
Location: TN-30 RG-09
SC-36 UL-J
1 - State

NMOCD Zone:OUTSIDE Hazard Ranking Score:00



## RATIONALE FOR RISK-BASED CLOSURE OF PRODUCTION PITS LOCATED OUTSIDE OF THE VULNERABLE ZONE IN THE SAN JUAN BASIN

This production pit location was ranked according to the criteria in the New Mexico Oil Conservation Division's Unlined Surface Impoundment Closure Guidelines and received a ranking score of zero. The estimated depth to groundwater is greater than 100-feet beneath ground surface (bgs), the pit is not in a well head protection area, and there are no surface water bodies within 1,000 horizontal feet of the pit location.

The primary source, discharge to the pit has been removed. There has been no discharge to the pits for at least 4 years and the pits have been closed for at least one year.

Each pit was backfilled with clean soil and graded in a manner to divert precipitation away from the excavated area. Minimal infiltration of rainfall is expected. Any rainfall that does infiltrate the ground surface must migrate through clean backfill before reaching the residual hydrocarbons.

There is no source material at the ground surface, so direct contact of hydrocarbons with livestock and the populous is not likely.

In general, outside of the vulnerable area and alluvial valleys, bedrock material is generally encountered within 20 feet of the ground surface. Bedrock material in the San Juan Basin consists of interbedded sandstones, shales and clays. According to Freeze and Cherry, 1979, the hydraulic conductivity of the bedrock material are as follows:

Sandstone  $10^{-9}$  to  $10^{-13}$  cm/sec Shale  $10^{-12}$  to  $10^{-16}$  cm/sec Clay  $10^{-12}$  to  $10^{-15}$  cm/sec

Based on this information, the residual hydrocarbons should not migrate to groundwater.

Natural process (bioremediation) are degrading the residual hydrocarbon to carbon dioxide and water and will continue until the source is gone, therefore minimizing any impact to the environment.

Based on the above information, it is highly unlikely that any source material will impact groundwater or ever find an exposure pathway to affect human health and therefore El Paso Field Services Company (EPFS) requests closure of this pit location.



## FIELD PIT SITE ASSESSMENT FORM ELPASOFIELDS

GENERAL	Meter: 75994 Location: DELHI STATE COM # 1X  Operator #: 0286 Operator Name: Conoco P/L District: BloomFIELD  Coordinates: Letter: 5 Section 36 Township: 30 Range: 9  Or Latitude Longitude  Pit Type: Dehydrator Location Drip: X Line Drip: Other:  Site Assessment Date: 4.28.94 Area: 10 Run: 22
SITE ASSESSMENT	NMOCD Zone:    Land Type: BLM
REMARKS	Remarks: ONLY PIT ON LOCATION. PIT IS DRY LOCATION IS UP ON A MESA AT THE BASE OF SOME CLIPPS, REDLINE AND TOPO CONFIRMED LOCATION TO BE OUTSIDE THE V.T.  PUSH IN

GERAL	Meter: 75994 Location: Delhi State Com #1X  Coordinates: Letter: S Section 36 Township: 30 Range: 9  Or Latitude Longitude  Date Started: 5-20-94 Area: 10 Run: 22
FIELD OBSERVATIONS	Sample Number(s): VW123  Sample Depth: 9' Feet  Final PID Reading 26> PID Reading Depth 9' Feet  Yes No  Groundwater Encountered (1) (2) Approximate Depth Feet
CLOSURE	Remediation Method:  Excavation
REMARKS	Remarks: EPNG line markers -4 lit rick
1	Signature of Specialist: Vale Wilsen



## FIELD SERVICES LABORATORY ANALYTICAL REPORT PIT CLOSURE PROJECT - Soil

## SAMPLE IDENTIFICATION

	SAMPLL	DENTILIOA	11011			
	Field II	ם		Lab ID		
SAMPLE NUMBER:				945257		
MTR CODE SITE NAME:	75994 5-20-94		N/A			
SAMPLE DATE TIME (Hrs):			0830			; !
SAMPLED BY:	N/A					
DATE OF TPH EXT. ANAL.:	5/24/94 N/A VG		5/24/94			•
ATE OF BTEX EXT. ANAL.:						<b>!</b>
TYPE DESCRIPTION:			Wen sand + clay			
REMARKS:			` ()		(	
	R	RESULTS				<del>.</del>
			<u> </u>			
PARAMETER	RESULT	UNITS			IFIERS M(a) V(mi)	
			DF	<u> </u>	M(g)	4/4111
BENZENE		MG/KG				<u> </u>
TOLUENE		MG/KG			<u> </u>	
ETHYL BENZENE		MG/KG				
TOTAL XYLENES		MG/KG		<del></del>		
TOTAL BTEX		MG/KG				1
TPH (418.1)	410	MG/KG			2.05	28
HEADSPACE PID	262	PPM				
PERCENT SOLIDS	90.02	%%				<del></del> -
	- TPH is by EPA Method 41				ntable	
Surrogate Recovery was at rative:	NIT-	% for this samp	nie All QA/QC	was acce	plable.	
= Dilution Factor Used						
$\mathcal{L}$	arth ~		Date:	6/16/0	94	
proved By: John Hi	<u>, , , , , , , , , , , , , , , , , , , </u>		<del></del>	7-7	_	

