

(May 1963)

**UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY**

SUBMIT IN TRIPPLICATE*
(Other instructions on re-
verse side)

Form approved
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

SF 078439

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Johnston-Federal

9. WELL NO.

10

10. FIELD AND POOL, OR WILDCAT

Blanco Mesaverde Field

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Section 12-T30N-R9W

12. COUNTY OR PARISH

San Juan

13. STATE

New Mexico

1.

OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

Union Texas Petroleum, A Division of Allied Chemical Corporation

3. ADDRESS OF OPERATOR

Suite 1010, 1860 Lincoln St., Denver, Colorado 80203

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*

See also space 17 below.)

At surface

SE NE Section 12-T30N-R9W (1700' FNL, 990' FEL)

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

5903 GL, 5914 KB

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

FULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

Well completion

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spud date: 3/25/69.

Total depth drilled: 5250 ft.

Surface casing: 10-3/4" 10.4#, 295 ft. set at 306 ft., cemented w/300 sx cement.

Intermediate casing: 7" 20#, 2425.03 ft. set at 2991 ft., cemented w/550 sx cement.

Production casing: 4-1/2" 9.5# liner set at 5247 ft. Top of liner at 2813 ft.


Cemented w/150 sx lite and 50 sx Class C neat cement.

No tests, no cores.

Perforations: 4339-44, 4428-31, 4435-42, 4448-54, 4496-4521, 4539, 4549, 4555, 4629, 4672-75, 4680, 4906-11, 4918, 4934-38, 4940-62, 4967, 4969, 4991, 5007, 5029.

Sand water fraced 4906-5029 w/50,000# sand and 50,400 gal. water

Sand water fraced 4339-4680 w/70,000# sand and 78,870 gal. water



18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Petroleum Engineer

DATE

May 19, 1969

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side