

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

SF 076129

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Pierce

9. WELL NO.

6

10. FIELD AND POOL, OR WILDCAT

Blanco Pictured Cliffs

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 17, T-30-N, R-9-W

N.M.F.M.

12. COUNTY OR PARISH

San Juan

13. STATE

New Mexico

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)1. OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

El Paso Natural Gas Company

3. ADDRESS OF OPERATOR

Box 990, Farmington, New Mexico - 87401

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

1720'N, 1840'E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

6226' GL

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETION

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

On 4-27-69 snadded well, drilled surface hole.

On 4-28-69 ran 7 joints 8 5/8", 24#, J 55 casing (228') set at ground level w/190 sacks of cement circulated to surface. W.O.C. 12 hours, held 600#/30 Minutes.

On 5-3-69 T.D. 3039', ran 97 joints 2 7/8", 6.4#, J-55 casing (3028') set at 3039' w/235 sacks of cement. W.O.C. until completion.

On 5-21-69 P.B.T.D. 3029', tested casing to 4000# O. K. Perf. Pictured Cliffs 2946-54' w/17 shots, 2962-68' w/16 shots. Frac w/30,000# 10/20 sand, 30,870 gal. water. Max. pr. 4000#, BHP 1700#, avg. tr. pr. 3600#, I.R. 16 BPM. Dropped 1 set of 17 balls, flushed w/756 gal. water. ISIP 400#, 5 Min. 200#, 15 Min. 20#, 30 Min -0-.

RECEIVED

MAY 23 1969

U. S. GEOLOGICAL SURVEY
FARMINGTON, N. M.

18. I hereby certify that the foregoing is true and correct

SIGNED Original Signed F. H. WOOD

TITLE Petroleum Engineer

DATE 5-22-69

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

*See Instructions on Reverse Side