

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

SP-079043

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Horace F. McKay

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Basin Data

11. SEC., T., E., M., OR BLK. AND
SURVEY OR AREA

NE/4 Section 28,

T-31-N, R-25-W

12. COUNTY OR PARISH

San Juan

13. STATE

New Mexico

1.

OIL
WELL ☐

GAS
WELL ☐

OTHER

Dry Hole

2. NAME OF OPERATOR

PAN AMERICAN PETROLEUM CORPORATION

3. ADDRESS OF OPERATOR

501 Airport Drive, Farmington, New Mexico 87401

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*

See also space 17 below.)
At surface

880' FNL & 1540' FNL, Unit "B"

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

GL 6391', RDB 6405'

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other)

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

ABANDON* ☒

CHANGE PLANS ☒

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐

FRACTURE TREATMENT ☐

SHOOTING OR ACIDIZING ☐

(Other)

REPAIRING WELL ☐

ALTERING CASING ☐

ABANDONMENT* ☐

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Revised procedure to permanently abandon subject well:

1. Spot cement plug 7700-7880' (15 sacks over perfs).
2. Spot cement plug 6350-6450' (7 sacks at Top Gallup).
3. Spot cement plug 5200-5300' (7 sacks at top Mesaverde).
4. Spot cement plug 3560-3660' (7 sacks at bottom of intermediate casing).
5. Spot cement plug 200' to surface (15 sacks).
6. Squeeze 4-1/2" - 7-5/8" annulus with 5 sacks cement.
7. Squeeze 7-5/8" - 10-3/4" annulus with 13 sacks cement.
8. Erect P&A marker and clean location for inspection.

NOTE: Above procedure approved verbally Mr. E. Schmidt November 16, 1970.

RECEIVED

NOV 18 1970

**U. S. GEOLOGICAL SURVEY
DURANGO, COLO.**

18. I hereby certify that the foregoing is true and correct

SIGNED

D. A. WATMAN

TITLE

Area Engineer

DATE

November 17, 1970

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.