Form 9-331 (May 1963)

16.

UNITED STATES DEPARTMENT OF THE INTERIOR verse side)

SUBMIT IN TRIPLICATE*
(Other instructions on re-

		Form Budge	approv t Bure NATION	ed. au N	o. 42	R14	:
١,	LEASE	DESIG	NATION	AND	SERI	AL NO	J

NM 03566

San Juan

New Mexico

GEOLOGICAL SURVEY

6484'GL

02020	 			
	 DEDODIC	\triangle	MACEL	C

	6. IF INDIAN, ALLOTTEE OR WRIBE NAME
SUNDRY NOTICES AND (Do not use this form for proposals to drill or to Use "APPLICATION FOR PER.	
	7. UNIT AGREEMENT NAME
OIL GAS WELL OTHER	8. FARM OR LEASE NAME
2. NAME OF OUTRATOR	Stewart
El Paso Natural Gas Company	9. WELL NO.
PO Box 990, Farmington, NM 87	11
4. LOCATION OF WELL (Report location clearly and in acc	rdance with any State requirements.*
See also space 1 (below.) 10001C 1500	E Aztec Pictured Cliffs
At surface 1000 5, 1300	11. SEC., T., R., M., OR BLK. AND SURVEY OR AKEA Sec. 20, T-30-N, R-10-W
	(Show whether DF, RT, GR, etc.) NMPM 12. COUNTY OR PARISH 13. STATE
14 PERMIT NO. 15. ELEVATIONS	(Snow whether br, ki, dk, etc.)

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:				SUBSEQUENT REPORT OF:			
TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL		PULL OR ALTER CASING MULTIPLE COMPLETE ABANDON* CHANGE PLANS	-	WATER SHUT-OFF FRACTURE TREATMENT SHOOTING OR ACIDIZING (Other) (NOTE: Report results of mul Completion or Recompletion R	REPAIRING WELL ALTERING CASING ABANDONMENT* tiple completion on Well eport and Log form.)		
(Other)					And dote of startin		

- 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *
 - TD 2910'. Ran 94 joints 2 7/8", 6.4#, JS production casing, 2900' set at 1-20-73 2910'. Baffle set at 2899'. Cemented with 450 cu.ft. cement. WOC 18 hours. Top of cement at 1450'.
 - PBTD 2899'. Tested casing to 4000#-OK. Perf'd 2764-84' and 2794-2814' 5-21-73 with 30 shots per zone. Frac'd with 30,000# 10/20 sand and 29,500 gallons treated water. Dropped one set of 30 balls each. Flushed with 680 gallons water.



MAY 2 3 1973

. <u></u>			
8. I hereby certify that the foregoing is true and correct	TITLE _	Drilling Clerk	DATE May 22, 1973
(This space for Federal or State office use)			
APPROVED BYCONDITIONS OF APPROVAL, IF ANY:	TITLE _	•	DATE