

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE
(Other instructions on reverse side)

Form approved.
B. Get Bureau No. 45 R1424.

5. LEASE DESIGNATION AND SERIAL NO.
NM 0607
6. IF INTER, ALLOTTEE OR TRUST NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different section.
(Use "APPLICATION FOR PERMIT—" for such proposals.)

1. ☐ OIL WELL ☒ GAS WELL ☐ OTHER

2. NAME OF OPERATOR

El Paso Natural Gas Company

3. ADDRESS OF OPERATOR

PO Box 990, Farmington, NM 87401

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface 940'N, 1140'E

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Sunray H

9. WELL NO.

4

10. FIELD AND POOL, OR WILDCAT

Blanco Pictured Cliffs Ext.

11. SEC., T., R., M., OR BLM. AND
SURVEY OR AREA

Sec. 11, T-30-N, R-10-W
NMPM

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

6541'GL

12. COUNTY OR PARISH

San Juan

13. STATE

New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

SUBSEQUENT REPORT OF:

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

1-15-73 TD 3333'. Ran 108 joints 2 7/8", 6.4#, JS production casing, 3322' set at 3333'. Baffle set at 3322'. Cemented with 448 cu.ft. cement. WOC 18 hours. Top of cement at 1200'.

5-24-73 PBTD 3322'. Tested casing to 4000#-OK. Perf'd 3234-54' and 3266-80' with 30 shots per zone. Frac'd with 30,000# 10/20 sand and 30,000 gallons treated water. Dropped one set of 30 balls. Flushed with 880 gallons water.

RECEIVED

MAY 29 1973

GEOLOGICAL SURVEY

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Drilling Clerk

DATE May 29, 1973

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY: