DISTRIBUTION SANTA FE	NEW MEXICO OIL CONSERVATION COMMISSION	Form C-103 Supersedes Old C-102 and C-103 Effective 1-1-65
U.S.G.S.  LAND OFFICE	3	State Fee. X  5. State Oil & Gas Lease No.
(DO NOT USE THIS FORM	SUNDRY NOTICES AND REPORTS ON WELLS A FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)	
I. OIL GAS WELL WELL	X OTHER-	7. Unit Agreement Name
	ral Gas Company	8. Farm or Lease Name Bruington 9. Well No.
PO Box 990.	Farmington, NM 87401	5  10. Field and Pool, or Wildcat
UNIT LETTER C	850 FEET FROM THE North LINE AND 1806 FEET FROM	Aztec Pictured Cliffs
THE West LIN	E, SECTION 5 TOWNSHIP 30N RANGE 11W NMPM.	
	15. Elevation (Show whether DF, RT, GR, etc.) 5774'GL	12. County San Juan
	Check Appropriate Box To Indicate Nature of Notice, Report or Oth SUBSEQUENT	
PERFORM REMEDIAL WORK  TEMPORARILY ABANDON  PULL OR ALTER CASING	PLUG AND ABANDON REMEDIAL WORK COMMENCE DRILLING OPNS. CHANGE PLANS CASING TEST AND CEMENT JOB X	ALTERING CASING PLUG AND ABANDONMENT
OTHER	OTHER Fracture Trea	tment
17. Describe Proposed or Comwork) SEE RULE 1103.	pleted Operations (Clearly state all pertinent details, and give pertinent dates, including o	estimated date of starting any proposed
6-19-73	TD 2364'. Ran 81 joints 2 7/8", 6.5#, J, production casin 2364'. Baffle set at 2353'. Cemented with 552 cu.ft. cemented of cement at 550'.	~
6 <b>-</b> 19-73	2364'. Baffle set at 2353'. Cemented with 552 cu.ft. cem	ent. WOC 18 hours. with 30 shots.
	2364'. Baffle set at 2353'. Cemented with 552 cu.ft. cemerope of cement at 550'.  Tested casing to 4000#-OK. PBTD 2353'. Perf'd 2230-54'. Frac'd with 24,000# 10/20 sand, 23,130 gallons treated was with 550 gallons water.	with 30 shots.
7 <b>-</b> 5-73	2364'. Baffle set at 2353'. Cemented with 552 cu.ft. cemented to 4000 to 550'.  Tested casing to 4000#-OK. PBTD 2353'. Perf'd 2230-54' Frac'd with 24,000# 10/20 sand, 23,130 gallons treated was with 550 gallons water.	ent. WOC 18 hours. with 30 shots.
7 <b>-</b> 5-73	2364'. Baffle set at 2353'. Cemented with 552 cu.ft. cemerope of cement at 550'.  Tested casing to 4000#-OK. PBTD 2353'. Perf'd 2230-54'. Frac'd with 24,000# 10/20 sand, 23,130 gallons treated was with 550 gallons water.	with 30 shots.

CONDITIONS OF APPROVAL, IF ANY: