

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPPLICATE*
(Other instructions on re-verse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

SF077764

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Schumacher

9. WELL NO.

13

10. FIELD AND POOL, OR WILDCAT

Undes. Gallup

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 17, T-30-N, R-10-W
N.M.P.M.

12. COUNTY OR PARISH 13. STATE

San Juan

New Mexico

1. OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

El Paso Natural Gas Company

3. ADDRESS OF OPERATOR

P. O. Box 990, Farmington, NM 87401

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

980'S, 1460'W

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

6387' GL

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

04-05-75 TD 6815'. Ran 156 joints 4 1/2', 10.5#, K-55 production casing; 6804' set at 6815'. Float collar set at 6799'. Stage tools set at 5095' and 5566'. Cemented first stage with 98 cu. ft. cement; second stage with 546 cu. ft. cement; third stage with 768 cu. ft. cement. WOC 18 hours. Top of cement at 250'.

05-01-75 PBDT 6799'. Tested casing to 4000#--OK. Perf'd 6440', 6454', 6484', 6496', 6528', 6548', 6561', 6594', 6634', 6713', 6734', and 6779' with 1 shot per zone. Frac'd with 70,000#--20/40 sand and 74,500 gallons nitrogen and slick water. Dropped no ball sets. Flushed with 4540 gallons water.

MAY 7 1975

18. I hereby certify that the foregoing is true and correct

SIGNED A. J. Drisco

TITLE Drilling Clerk

DATE May 5, 1975

(This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

TITLE _____

DATE _____

*See Instructions on Reverse Side