Form 9-331 (May 1963)

16.

(Other)

UNITED STATES

NOTICE OF INTENTION TO:

SUBMIT IN TRIPLICATE* (Other instructions on reForm approved. Budget Bureau No. 42-R1424

REPAIRING WELL

SUBSEQUENT REPORT OF:

	DEPARTM G	SF078201A 6. IF INDIAN, ALLOTTEE OR TRIBE NAME			
	SUNDRY NOTION (Do not use this form for propositive "APPLICA"				
ι.				7. UNIT AGREEMENT N	AME
	OIL GAS WELL OTHER			8. FARM OR LEASE NA	V.E
2.	NAME OF OPERATOR			*· **	JI E
	El Paso Natural Gas Con	mpany		Riddle	
3.				9. WELL NO.	
٠.	P. O. Box 990, Farming	ton, NM 87401		3A	
4.	LOCATION OF WELL (Report location cl	early and in accordance with any	State requirements.	Blanco Mesa Verde	
	See also space 17 below.) At surface				
			N. M. W.	11. SEC., T., R., M., OR SURVEY OR ARE	A
	1680'S, 1590'E			Sec. 10, T-30-N, R-9-W	
				N.M.P.M.	
11	PERMIT NO. 15. ELEVATIONS (Show whether DF, RT, GR, etc.)		12. COUNTY OR PARIS	H 13. STATE	
14	l, PERMIT NO.	6126' GL		San Juan	New Mexico
		1 017.0 314		1 Carr Gami	1

WATER SHUT-OFF PULL OR ALTER CASING TEST WATER SHUT-OFF ALTERING CASING FRACTURE TREATMENT MULTIPLE COMPLETE FRACTURE TREAT ARANDON MENT* SHOOTING OR ACIDIZING ABANDON* SHOOT OR ACIDIZE (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) REPAIR WELL

CHANGE PLANS

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

- 02-17-76 TD 3121'. Ran 9 joints 7", 23#, KE intermediate casing, 3109' set at 3121' set at 3121'. Cemented with 348 cu. ft. cement. WOC 12 hours, held 1200#/ 30 minutes. Top of cement at 1600'.
- TD 5531'. Ran 59 joints 4 1/2", 10.23#, X-52EE casing liner, 2572' set 02-21-76 at 2959-5531'. Float collar set at 5514'. Cemented with 453 cu. ft. cement. WOC 18 hours.
- PBTD 5514'. Tested casing to 4000#, OK. Perf'd 4537', 4574', 4615' 03-15-76 4654', 4668', 4692', 4696', 4722', 4736', 4751', 4763', 4817', 4876', 4953', 4987', 4998', 5078' with 18 holes. Frac'd with 72,000#--20/40 sand and 76,986 gallons water. No ball sets dropped. Flushed with 5670 gallons water. Perf'd 5129', 5146', 5162', 5176', 5189', 5209', 5217', 5244', 5267', 5281', 5312', 5401', 5421', 5451' with 14 holes. Frac'd with 66,000#-20/40 sand and 76,238 gallons water. No ball sets dropped. Flushed with 6384 gallons water.

SIGNED SIGNED	TITLE	Drilling Clerk	DATE March 17,	1976
(This space for Federal or State office use)	· · · · · · · · · · · · · · · · · · ·			*
APPROVED BY	TITLE _	<u> </u>	DATE 1	<u> </u>