

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)Form approved
Budget Bureau No. 42-R1421.

5. LEASE DESIGNATION AND SERIAL NO.

SF076934-A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Mansfield

9. WELL NO.

1-A

10. FIELD AND POOL, OR WILDCAT

Blanco Mesa Verde

11. SEC., T., R., M., OR BLM. AND
SURVEY OR AREA

Sec. 29, T-30-N, R-9-W

N.M.P.M.

12. COUNTY OR PARISH 13. STATE

San Juan

New Mexico

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, OR, etc)

6136' GL

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

SUBSEQUENT REPORT OF:

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

04-13-75 TD 3169'. Ran 76 joints 7", 20#, K-55 intermediate casing, 3157' set at 3169'. Cemented with 419 cu. ft. cement. WOC 12 hours, held 1200#/30 minutes. Top of cement at 1600'.

04-17-75 TD 5418'. Ran 73 joints 4 1/2", 10.5#, K-55 casing liner, 2407' set from 3011-5418'. Float collar set at 5401'. Cemented with 419 cu. ft. cement. WOC 18 hours.

05-14-75 PBTD 5400'. Tested casing to 4000#, OK. Perf'd Point Lookout 5033', 5044', 5060', 5074', 5090', 5114', 5142', 5168', 5202', 5260', 5296', 5316', 5342', 5361', 5381 with 1 shot per zone. Frac'd with 11,000# 100 mesh sand and 108,000#--20/40 sand and 123,900 gallons treated water. Dropped no ball sets. Flushed with 6000 gallons water.

05-17-75 Refrac'd Point Lookout with 40,000#--20/40 sand and 39,984 gallons water. No ball drops. Flushed with 6720 gallons water.

05-18-75 Perf'd Menefee and Cliff House 4418', 4437', 4471', 4492', 4552', 4660', 4683', 4710', 4735', 4782', 4836', 4863', 4893' with 1 shot per zone. Frac'd with 90,000#--20/40 sand and 81,564 gallons treated water. No ball drops. Flushed with 5964 gallons water.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Drilling Clerk

DATE May 30, 1975

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side