UNITED STATES SUBMIT IN TRIPLICATE*
DEPARTMENT OF THE INTERIOR (Other instructions on reverse side) Form 9-331 (May 1963) Form approved. Budget Bureau No. 5. LEASE DESIGNATION AND SERIAL NO. GEOLOGICAL SURVEY SF045646-A 6. IF INDIAN, ALLOTTER OR TRIBE NAME SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir, Use "APPLICATION FOR PERMIT--" for such proposals.) 7. UNIT AGREEMENT NAME WELL WELL X OTHER 2. NAME OF OPERATOR 8. FARM OR LEASE NAME El Paso Natural Gas Company Mansfield. 3. ADDRESS OF OPERATOR 9. WELL NO. P. O. Box 990, Farmington, NM LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) 10. FIELD AND POOL, OR WILDCAT At surface Blanco Mesa Verde 11. SEC., T., R., M., OR BLE. AND SUBVEY OR ABEA 1700'S, 1050'E Sec. 29, T-30-N, R-9-W N.M.P.M. 14. PERMIT NO. 15. ELEVATIONS (Show whether DF, RT, GR, etc.) 12. COUNTY OR PARISH 13. STATE 5862' GL San Juan New Mexico 16. Check Appropriate Box To Indicate Nature of Notice, Reports Other Data 0/2 NOTICE OF INTENTION TO: BSEQUENT REPORT OF: PULL OR ALTER CASING TEST WATER SHUT-OFF WATER SHUT-OFF REPAIRING WELL. FRACTURE TREAT MULTIPLE COMPLETE FRACTURE TREATMENT ALTERING CASING SHOOT OR ACIDIZE ABANDON* SHOOTING OR ACIDIZING ABANDON MENT* REPAIR WELL CHANGE PLANS (Other) _ (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) (Other)

42-R1424.

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

- 04-03-75 TD 2907'. Ran 71 joints 7", 20#, K-55 intermediate casing, 2895 ' set at 2907'. Cemented with 366 cu. ft. cement. WOC 12 hours, held 1200#/30 minutes. Top of cement at 1400'.
- 04-07-75 TD 5158'. Ran 57 joints 4 1/2", 10.5#, K-55 casing liner, 2415' set 2743-5158'. Float collar set at 5141'. Cemented with 417 cu. ft. cement. WOC 18 hours.
- 05-23-75 PBTD 5141'. Tested casing to 4000#--OK. Perf'd Point Lookout 4774', 4787'. 4808', 4820', 4830', 4856', 4874', 4888', 4961', 4972', 5019', 5050', 5064', 5091', 5104' with 1 shot per zone. Frac'd with 12,000# 100 mesh sand, 116,000#--20/40 sand and 133,980 gallons treated water. No ball drops. Flushed with 6250 gallons water. Perf'd Menefee 4449', 4462', 4491', 4524', 4573', 4609', 4618', 4639', 4658', 4674' with 1 shot per zone. Frac'd with 65,000#--20/40 sand and 71,400 gallons treated water. No ball drops. Flushed with 5960 gallons water. Perf'd Cliff House 4160', 4178', 4197', 4210', 4230', 4300 with 1 shot per zone. Frac'd with 42,000#--20/40 sand and 48,050 gallons treated water. No ball drops. Flushed with 5700 gallons water.

18. I hereby certify that the foregoing is true and correct SIGNED . Success		Drilling Clerk	DATE	May 30, 1975
(This space for Federal or State office use)				
APPROVED BYCONDITIONS OF APPROVAL IF ANY:	TITLE		DATE	