

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.
5. LEASE DESIGNATION AND SERIAL NO.

ST-078505

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Seymour

9. WELL NO.

6-A

10. FIELD AND POOL, OR WILDCAT

Blanco Mesaverde

11. SEC. T. R. M., OR BLK. AND

Sec. 14, T-31N, R-9W, N4PM

12. COUNTY OR PARISH

San Juan

13. STATE

New Mexico

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. ☐ OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

Southern Union Production Company

3. ADDRESS OF OPERATOR

P. O. Box 808, Farmington, New Mexico 87401

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)

At surface
795' North line & 1780' West line.

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

6507 ft. G.L.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐ PULL OR ALTER CASING ☐
FRACTURE TREAT ☐ COMPLETE ☐
SHOOT OR ACIDIZE ☐ ABANDON* ☐
REPAIR WELL ☐ CHANGE PLANS ☐
(Other) ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐ REPAIRING WELL ☐
FRACTURE TREATMENT ☒ ALTERING CASING ☐
SHOOTING OR ACIDIZING ☐ ABANDONMENT* ☐
(Other) **Supplementary History** ☒

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1. Drilled 8-3/4" Intermediate hole to T.D. of 3550 ft. R.K.B.
2. Ran I.E.S. Log.
3. Ran 8 1/2" 7", 26.0#, Intermediate casing. Landed at 3550 ft. Cemented casing with 385 sacks cement. Plug down at 10:00 P.M., 8/17/75.
4. Drilled 6-1/8" hole to T.D. of 6000 ft. RKB. Reached T.D. on 8/21/75.
5. Ran Gamma-Ray Density and Neutron logs.
6. Ran 7 1/2" 4-1/2", 10.5# casing as liner. Top of liner at 3400 ft. Bottom at 5960 ft. Cemented liner with 310 sacks cement. Plug down at 3:50 P.M., 8/21/75.
7. Moved in and rigged up Completion Rig.
8. Ran 2-3/8" tubing and bit. Cleaned out to P.B.T.D. of 5934 ft. R.K.B.
9. Tested casing to 2600 psi. Test OK.
10. Ran Cement Bond and Correlation logs.
11. Perforated Point Lookout 1 shot/ft. from 5630 - 5666, 5702-5712 & 5852 - 5856 ft. Total of 50 holes.
12. Sand Water fraced perforations #/60,000# 20-40 sand and 60,000 gallons of water.
13. Set Howco 4-1/2" Bridge Plug at 5610 ft. R.K.B. Tested plug to 2700 psi. Test OK.
14. Perforated Manefee 1 shot/ft. from 5408-5412, 5446-5450, 5484-5488, 5498-5502 and 5586-5590 ft. R.K.B. Total of 20 holes.
15. Sand Water Fraced perforations #/45,000# 20-40 sand and 45,000 gallons of water.
16. Set Howco 4-1/2" Bridge Plug at 5375 ft. R.K.B. Tested plug to 2700 psi. Test OK.
17. Perforated Cliff House 1 shot/ft. from 5271 - 5308 ft. Total of 37 holes.

18. I hereby certify that the foregoing is true and correct

SIGNED **Don R. Collier** Original signed by **Office Manager** TITLE

DATE **October 14, 1975**

(This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

TITLE _____

DATE _____

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

18. Sand-water fraced perforations w/60,000# 20-40 sand and 60,000 gallons of water.

19. Ran 2-3/8" tubing and bit. Drilled out bridge plug at 5375 ft. and bridge plug at 5610 ft. Cleaned out well to P.B.T.D.

20. Ran 174 lbs. 2-1/16", I.J. production tubing. Landed at 5644 ft. R.X.B.

21. Well completed 10/6/75.