UNITED STATES SUBMIT IN DUPLICATE. DEPARTMENT OF THE INTERIOR

(See other instructions on reverse side)

Budget Buréau No. 42-R358.8.

5. LEASE DESIGNATION AND SERIAL NO.

		GEUL	JUGICA	AL SURV	EY					SF	07838	5-A		
WELL CO	OMPLETIC	ON OR	RECON	MPLETIO	N R	EPORT	AN	D LC)G*	6.	IF INDIA:	N, ALLO	TTEE OR TRIBE	FAME
ia. TYPE OF W		OIL U	WELL 2			ther					UNIT AGE	EEMEN	T NAME	
b. TYPE OF CO						rtuer		*		- "			1 1144	
NEW WELL X	OVER	EN DEEP-	PLCG BACK	DIFF. ESVR.] o	ther				— ;	FARM OR		NAME	—
El Paso Na		s Compan	IV.								well			
3. ADDRESS OF OR		o Compan	.,		· 					2A	WELL NO	•		
P. O. Box	990, Farr	mington,	NM	87401				1	Ì	J '		ND POO	L, OR WILDCAT	
4. LOCATION OF W	ELL (Report lo	cation clearly	y and in a	ccordance wit	any	State requi	remen	te)*	7	,			Verde	
	985'S, 1			į		Ville Co.	10		:	11. C-	SEC., T., OR ALEA	R., M.,	OR BLOCK AND SU	TVET
At top prod. 1	nterval reporte	d below			•	1.11	1 ***	•	1) Se	c. 25 M.P.M	, i	30-N, R-8-	W
At total depth	ı						•	· j · · · · · · · · · · · · · · · · · ·		111.1	M. F. M	•		
				14. PERMIT	No.	,	DATE	ISSUED		12.	COUNTY PARISH	OR	13. STATE	
5. DATE SPUDDED	16 DITE T	A RELOWER	17 2.55	COMPL. (Rea			,				n Juan	1	New Mex	ico
03-12-76	03-24	,		17-20-76	ay to 1	prod.) 18		145 '		B, RT, GR	, ETC.)*	19. 1	ELEV. CASINGHEA	>
0. TOTAL DEPTH, MI	· ·	PLUG, BACK T		TVD 22. IF	MULTI	PLE COMPL.			TERVAL	S RO	TARY TOO	LS	CABLE TOOLS	
5572'		55551		į	W MWN			DB	ILLED I	Y	0-5572		J	
4. PRODUCING INT		HIS COMPLET	TON-TOP,	BOTTOM, NAM	E (MD	AND TVD)	•			'		25	. WAS DIRECTION	AL
4748-5482'	(MV)												NO NO	
6. TYPE ELECTRIC	AND OTHER LO	GS_RUN		·								27 w	AS WELL CORED	
IGR; FDC-G	R; Cement	Bond L	og; Te	mp. Surv	ey								Yes	
28.			CASI	G RECORD			s set in	well)						_
9 5/8"	WEIGHT,	LB./FT.	DEPTH SET		HOLE					NG RECOR	D		AMOUNT PULLI	D
7"	32.3#		219' 3379'		3 3/ 8 3/		1	4 cu 9 cu						
			3313		0 3/	4	32	9 Cu	. IL	•				
							<u> </u>							—
9.		LINER I	RECORD					30.		TUBIN	G RECO	RD		
4 1/2''	3196 [†]	воттом 5572¹		AOO CH	- 1 -	SCREEN (MI	D)	SIZE			SET (M)	9)	PACKER SET (M	D)
4 1/2	3130	3372		409 cu.	IL			2 3/8		54	165			
1. PERFORATION RE	CORD (Interval	size and no	imber)	711 1966	,	32.	ACI	D. SHO	r. FRA	CTURE	CEMENT	SOLE	EEZE, ETC.	_
4896',4979	',5013',5	024',50	35',50	70' with	, -	DEPTH INT							ATERIAL USED	
per zone.	51821-9	0',5192	'-5202	52081-	321,	4748	- 507	0'	60	,000	sand	; 65	,500 gal	<i>ī</i> tr
,4758',4768 ,4896',4979 per zone. 50',5254'- 77',5406'-	70,3203 14',5427'	-34',54	74'-82	' with	- 3 <u> </u> -	· 5182	-548	2!	75	000±	sand	; 10	06,200 gal	wt.
ots per zon	e.				-				-			 -		
3.*				P	RODUC	CTION			!					_
ATE FIRST PRODUCT	TION PA			owing, gdXXX			XXXX	*XXX	wex -	· · · · · ·	WELL S	TATUS	(Producing or	
ATE OF TEST	HOURS TEST		Atter	Frac Gau	<u> </u>	4533						•••	SI	
-76		- Choi	12 0122	TEST PERIO		IL-BBL.	1	GAS—M	CF.	WAT	ER—BBL.	9	SAS-OIL BATIO	
OW. TUBING PRESS.	CASING PRES		ULATED	OIL-BBL.		GAS3	CF.	4	TATE		\	OIL GR	AVITY-API (CORR.	_
)	SI 668	-	OUR BATE			1		KL	1,5	*	-		(00	
4. DISPOSITION OF	AS (Sold, used	for fuel, vent	ed, etc.)			<u> </u>	1				WITNESS			_
5. LIST OF ATTACH	MENTS	-					1	AU	<u> 2</u>	1976		Rog	er Hardy	
		_					1	all i	A 114	COM	. /		-	
6. I hereby certify	that the foreg	oing and att	ached info	ormation is co	mplete	and correc	et as c	termi	HSE	n al ar	llable re	cords	· · · · · · · · · · · · · · · · · · ·	_
\ /	1		Luies					Cler						

General: This form is designed for submitting a complete and correct well completion report and log on all types of lands and leases to either a Federal agency or a State agency. or both, pursuant to applicable Federal and/or State laws and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office. See instructions on items 22 and 24, and 33, below regarding separate reports for separate completions. If not filed prior to the time this summary record is submitted, copies of all currently available logs (drillers, geologists, sample and core analysis, all types electric, etc.), formation and pressure tests, and directional surveys, should be attached hereto, to the extent required by applicable Federal and/or State laws and regulations. All attachments

Hem 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State should be listed on this form, see item 35.

Herm 18: Indicate which elevation is used as reference (where not otherwise shown) for depth measurements given in other spaces on this form and in any attachments.

Herms 22 and 24: If this well is completed for separate production from more than one interval zone (multiple completiou), so state in item 22, and in item 24 show the producing interval, or intervals, top(s), bottom(s) and name(s) (if any) for only the interval reported in Item 33. Submit a separate report (page) on this form, adequately identified, for each additional interval to be separately produced, showing the additional data pertinent to such interval.

Herm 29: "Specks Comput": Attached supplemental records for this well should show the details of any multiple stage cementing and the location of the cementing tool. or Federal office for specific instructions.

item 33: Submit a separate completion report on this form for each interval to be separately produced. (See instruction for items 22 and 21 above.)

4845 4899 Recovered 4899 4936 Recovered 4936 A999 Recovered 4996 5043 Recovered 5043 5090 Recovered 5090 5114 Recovered 5114 Recovered	NOTAL MARKA	Top	RVATION TOP BOTTOM	DESCRIPTION, CONTENTS, ETC.		TOP	P.
4899 Recovered 52' 4936 Recovered 33' 4999 Recovered 60' 5043 Recovered 39' 5073 Recovered 29.3' 5114 Recovered 13.5' 5134 Recovered 13.8'					20216		TRUE VERT. DEFTH
4899 4936 Recovered 33' 4996 4999 Recovered 60' 5043 Recovered 29.3' 5073 Recovered 29.3' 5090 S114 Recovered 13.5' 5114 S134 Recovered 19.8' Recovered 19.8'	Mesa Verde	4845	4899				-
4999 Recovered 60' 5043 Recovered 39' 5073 Recovered 29.3' 5090 Recovered 13.5' 75114 Recovered 23' 8134 Recovered 19.8'		4899	4936				
5043 Recovered 39' 5073 Recovered 29.3' 5090 Recovered 13.5' 5114 Recovered 23' 5134 Recovered 19.8'		4936	4999		W	4741	
5073 Recovered 29 5090 Recovered 13 5114 Recovered 23 5134 Recovered 19		4996	5043	. 39	PL	5174	
5090 Recovered 13 5114 Recovered 23 5134 Recovered 19		5043	5073	29			-
5114 Recovered 23 5134 Recovered 19		5073	5090	13			-
L4 5134 Recovered 19		5090	5114	23			
		5114	5134	. 19			
							•
						. 1	
			• ·			-	
		_				•	. 5
	•		•	-		-	
	-						