

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.
USA-NM-013686

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR
Tenneco Oil Company

3. ADDRESS OF OPERATOR
1860 Lincoln St., Denver, Colorado 80203

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

1840' FNL & 1660' FWL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)
6023' GL

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Pritchard

9. WELL NO.
1A

10. FIELD AND POOL, OR WILDCAT
Blanco Mesa Verde

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec.1, T30N, R9W

12. COUNTY OR PARISH
San Juan

13. STATE
New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

6-23-75 - Spudded 13 3/4" hole 3:15 A.M. Drilled to 217'. Ran and cemented 5 JTS 9 5/8" 36# K55 casing. Cemented with 300 sacks. Class B w/3% CaCL. Plug down 12:45 P.M. 6/23/75 Float held WOC to 12:45 A.M. 6/24/75 Drilled 8 3/4" hole to TD 3208' 5:30 P.M. 6/26/75. Ran 78 JTS of 7" 23#,K-55 LT & C casing. Total 3192' set at 3206'. Cemented with 450 sacks 65/35 lite poz with 12% gel followed by 50 sacks CLA with 3% CaCL w/ 1/4 sx/lb. B-29. Circulated to pit. Plug down at 10:00 A.M. 6/27/75 Set slips; welder cut off casing, WOC & NU PU 2 7/8" dp. Not enough gas pressure to blow well. Rented compressor. Drilled float, 4' cement in sleeve, blow hole to 4:00 P.M.

RECEIVED

JUL 17 1975

U. S. GEOLOGICAL SURVEY
WASHINGTON, D. C.

18. I hereby certify that the foregoing is true and correct

SIGNED

Red G. Drake

TITLE Production Clerk

DATE 7/14/75

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE