

RECEIVED

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

JAN 26 1987

BUREAU OF LAND MANAGEMENT
FARMINGTON RESOURCE AREA

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☒ gas well ☐ other ☐

2. NAME OF OPERATOR

Texas Eastern Developments, Inc.

3. ADDRESS OF OPERATOR

P. O. Box 2521, Houston, Texas 77001

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 2310' FNL, 2310' FWL
AT TOP PROD. INTERVAL: 1588'
AT TOTAL DEPTH: 1728'

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON ☒
(other) ☐

SUBSEQUENT REPORT OF:

☐
☐
☐
☐
☐
☐
☐
☐
☐
☐
☒

P&A

RECEIVED

JAN 16 1987

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

BUREAU OF LAND MANAGEMENT
FARMINGTON RESOURCE AREA

5. LEASE

N00-C-14-20-5337

6. INDIAN, ALLOTTEE OR TRIBE NAME

Navajo Allotted

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Tall-Jim

9. WELL NO.

One

10. FIELD OR WILDCAT NAME

Verde-Gallup

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA T-30N, R-16W, NW 1/4 Sec. 7

12. COUNTY OR PARISH

San Juan

13. STATE

N.M.

14. API NO

15. ELEVATIONS (SHOW DF, KDB, AND WD)

5,440GR

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

The well was drilled some time in 1976 and has not had any production since then, to our knowledge.

WELL DATA

Spud TD 1800' Hole Size 6 1/4" Csg: 10" @ 25' cmt'd to surface
7" @ 350' cmt'd w/shoulder
4 1/2" @ 1600' cmt'd w/30 sx

METHOD OF PLUGGING

Remove tubing, squeeze Verde-Gallup Sand (1800-1600') w/50 sx neat cmt, fill 4 1/2" csg 1300-0' w/9.5#/gal mud. Set 50 sx neat cmt plug 490' to surface.

Set marker. Squeeze cement from 0-440' down backside (7"-4 1/2" granules)

Subsurface Safety Valve: Manu. and Type Set @ FL

18. I hereby certify that the foregoing is true and correct

SIGNED M. N. Hinds

TITLE Drlg. Supt.

DATE

APPROVED

(This space for Federal or State office use)

AS AMENDED

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE

FEB 04 1987

OIL CON. DIV.

*See instructions

NMOCC

DATE

FEB 02 1987

AREA MANAGER