NEW MEXICO OIL CONSERVATION COMMISSION

NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

		N)KTHWEST	NEW MEXICO PACA	ER-1	LEA NAGE	IESI	Well
perator	enneco Oil Co	ompan	У	Le	ase	Fl	orance	No. 9A
ocation								
f Well: Uni	tSec];	<u></u> T	wp. <u>30N</u>	Rge	•	9W	County	San Juan
				Type of Prod.		Method (of Prod.	Prod. Medium
	Name of Reser	voir	or Pool	(Oil or Gas)	(<u>F</u>	flow or	Art. Lift)	(Tbg. or Csg.)
per	Dietu	and C	1 <i>i ££</i>	Gas		Flow		Tubing
mpletion _	on Pictured		1111	Gas	110			Tubing
wer Mesa Verd				Gas		Flow		Tubing
mpletion	nesa .	- dc		LOW SHUT-IN PRE				Tubing
177	0/10/8	1	Length			SI pres	s.	Stabilized?
oper Hour, date 9/10/84 ompl Shut-in 4:00 p.m.			time shut-in 72 hours			psig		(Yes or No) ves
ower Hour, date 9/10/84			Length		SI pres			Stabilized?
	in 4:00 p		_	t-in 72 hours		psig	360	(Yes or No)no
<u> </u>		· · · · · · · · ·						
numenced at	(hour, date)	۶ 9/1	3/84	4:00 p.m.			oducing (Uppe	r or Lower): lower
Time	menced at (hour, date)* 9 Time Lapsed time		Pres	sure	Pro	d. Zone	Remarks	
our, date)	since*	Uppe:	r Compl.	Lower Compl.	Ter	mp	Rem	arks
9/14/84		}	:					
1:00 p.m.	24 hours	28	0	300				
9/15/84			_	000				
1:30 a.m.	44 hours	28	U	280				
	 	 			 			
		1			L			
	1	1					_	
					<u> </u>			
					1			
oduction ra	te during te	st				TT	Comp	CUB
1:	BOPD b	ased	on	Bbls. in_	- M	Hrs	Gra	GOR
as:58	39	MCFPD	; Tested	thru (Orifice of SHUT-IN PR	ECCII	BE DATA	Meter	
) - A -		Length		5000	SI pres	SS.	Stabilized?
Upper Hour, date Compl Shut-in			time shut-in			psig		(Yes or No)
ower Hour, date			Length of		SI press.			Stabilized?
ompl Shut	-in		time shu			psig		(Yes or No)
ompri onuo				FLOW TEST N	0.2			
ommenced at	(hour, date)	××						er or Lower):
Time Lansed time		1	Pressure		Prod. Zone		Remarks	
nour, date)	since **	Uppe	r Compl.	Lower Compl.	T	'emp.	<u> </u>	arks
].							
					i		100 F . (* 100 doc)	
 		┼			+			
					1		શાંધો માન	
	 	+		 			JAN 1 6	1985
	1				İ		Oll Con	1. 51V
	+	+			T			
					!		DIST.	<u> </u>
	1	1			:			
				<u></u>	!		<u> </u>	
roduction r	ate during te	st				••	0	COB
il:	BOPD b	ased	on	Bbls. in_		nrs.	urav.	GOR
as:		_MCF	PD; Teste	d thru (Orifice	or	meter):		
emarks:								
		•						
	110- Ab-A Ab-	1-6	armet fon	harein contains	d 1	s true A	nd complete to	o the best of my
nereby cer	tlly that the	ותתי	OLEMPN TOIL	INTATE COMPANY				•
nowreage.	INN 1 2 19	85		Operat	cor	Tenneco	Oil Company	
nametred :	JAN TO 12	J J	19	operac	 _	· · · · · · · ·	\	Katharine Jenkir
pproved:	JAN 18 19 Oil Conservat	ion	Commissio	n By X	the	rine >	Dil Company Jeschies	Natharine Jenkin
HON HORLOO	022 0011010					Agent	/	
Origin	al Signed by CHARL	ES GHO	JE2UN	Title		Agenti		
J								
itle DFPHT	Y OIL & GAS INSPE	CTOR. I	DIST_#3	Date_		December	<u> 31, 1984</u>	

MORTHWEST MEN MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually-thereafter as prescribed by the order authorising the multiple completion. Buch tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Commission.
- At least 72 hours prior to the commencement of any packer leakage test the operator shall notify the Commission in writing of the exact time the test is to be commenced. Offest operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: If, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a nipeline connection the flow period shall be three bours.
- 5. Following completion of Flow Test No. 1, the well shall again be shutin, in accordance with Paragraph 3 above.
- 6. Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.

- 7. Pressures for gas-zone tests must be measured on each mone with a deadweight pressure gauge at time intervals as follows: 3-hour tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.
- 24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously seasured and recorded with recording pressure gauges, the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.
- 8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Commission or Northwest New Mexico Packer Leakage Test Form Revised 11-1-58, with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only). A pressure versus time curve for each zone of each test shall be constructed on the reverse side of the Packer Leakage Test Form with all deadweight pressure points taken indicated thereon. For oil zones, the pressure curve should also indicate all key pressure changes which may be reflected by the recording gauge charts. These key pressure changes should also be tabulated on the front of the Packer Leakage Test Form

