9-19-30N-9W

OIL CONSERVATION DIVISION NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

	tor: AMOCO	O PRODUCTION 96	COMP			ANSFIELD 00 County:SAN		£73
	NAME RE	SERVOIR OR F	OOL		TYPE PROD	METHOD PR	OD M	EDIUM PROD
UPR COMP	MANSFIEL	D 001A FT 9	5196		GAS	FLOW		TBG
LWR COMP	MANSFIEL	D 001A MV 4	44821		GAS	FLOW		TBG
	1	PRE	-FLOW	SHUT-IN P	RESSURE DA	ATA		
	Hour/Da	te Shut-In	Leng	th of Time	Shut-In	SI Press.	PSIG	Stabilzed
UPR COMP	11/02/9	5		72	,	161	7	Seal
LWR COMP	11/02/9	5		72		167	,	wa
	.	· · · · · · · · · · · · · · · · · · ·		FLOW TEST	DATE NO.1		<u></u>	
Comme	nced at (hour,date)*	··			Zone I	roduci	ng (Upr/Lwr)
(hc	TIME our, date)	LAPSED SINCE		PRE Upper	SSURE Lower	Prod Temp.	R	EMARKS
1	.1/0 2 /95	Day	 L	/41	160		Bot	h Zones SI
1	.1/0 \$ /95	Day	2	157	160		Bot	h Zones SI
1	1/08/95	Day	3	167	160		Bot	h Zones SI
1	1/0 9 /95	Day	1	167	167		Llower	I lower 7pm
1	.1/0 % /95	Day	5	178	90			/ 11 0
	1/0 9 /95	Day	5	179	50			И
Produ Oil: Gas:			based MFCPI	on BD:Tested th	BLs in eu (Orifi	ce or Mete	Gra :METE	v GOR
UPR COMP	Hour, Da	ate SI Len	gt.h o	f Time SI	SI Press		tabiliz	ed (yes/no)
LWR COMP							NOV 2 7	1395 U
		I	(Co	ntinue on r	reverse si	de) (0)	HOD ! Tale	

TEST	

Zone preducing Alpper or Lowers

	LAPSED THEE	PREI		PROG. ZOKE	
44	\$MCE **	Vepur Complettus	Lower Completion	154	REMARKS
					•
		1	1		
		<u> </u>			
			1		
					
912 00	during test				
ou late	amme con				
	-			•	
	-	PD based on	Bbls. is	1 Hours	GnvGOR
	BOI				Grav GOR_
	BOI				
	BOI	мс	FPD: Tested thru	(Orifice or Meter	Grav GOR _
	BOI	мс	FPD: Tested thru	(Orifice or Meter	
	BOI		FPD: Tested thru	(Orifice or Meter	
	BOI	мс	FPD: Tested thru	(Orifice or Meter	
J:	BOI	мс	FPD: Tested thru	(Orifice or Meter	;):
:	BOI	мс	FPD: Tested thru	(Orifice or Meter	
s:	that the informa	tion besein contai	FPD: Tested thru	Onifice or Meter	st of my knowledge.
certify	that the informa	tion besein contai	FPD: Tested thru	Onifice or Meter	;):
s:	that the informa	мс	FPD: Tested thru	omplete to the be	st of my knowledge.
s:	that the information	tion berein contain	FPD: Tested thru	omplete to the be	st of my knowledge.
y certify ed Mexico	that the information NOV 2	tion berein contain	FPD: Tested thru	omplete to the be	st of my knowledge.
s:	that the information NOV 2	tion berein contained birision 7 1995	FPD: Tested thru	omplete to the be	st of my knowledge.

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

1. A packer leakage test shall be commenced on each multiply complexed well within seven days after screaf complexion of the well, and annually thereafter as prescribed by the order surhorizing the moltiple complexion. Such test shall also be commenced on all multiple complexions within seven days following recomplexion and/or chemical or fracture treatments, and whenever remedial work has been done on a well during which the packet or the rubing have been disrurbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.

red at from, dated * *

- At least 72 hours prior to the commencement of any pocker leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced, Offset operators shall also be so notified.
- The packer leakage sext shall commence when both zones of the dual completion are shur-in for previous subdistation. Both zones shall remain shut-in until the well-head pressure in each has subdisted, provided however, that they need not remain shut-in more than seven doys.
- 4. For Flow Test No. 1, one some of the dual completion shall be produced at the normal rate of production while the other some remains short-in. Such next shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Nose: if, on an initial pather leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three bours.
-). Following completion of Flow Test No. 1, the well shall again be shot-in, in accordance with Paragraph 3 above.
- 6. Flow Test'No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same to for Flow Test No. 1 except

- that the previously produced 2000 shall remain abus-in while the 2000 which was previously abot-in it produced.
- 7. Pressures for gas-some term must be measured on each some with a deadweight pressure geoge at time intervals as follows: 3 hours term; immediately prior to the beginning of each flow-period, at fateen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period, 7-day term; immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and introductly prior to the conclusion of each flow period, Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

14-hour of some usus: all pressures, throughout the conice test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least raire, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gus-oil or on oil-gus dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gus some.

8. The results of the above-described ness shall be filed in triplicate within 15 days after completion of the nest. Tests shall be filed with the Assec Dount Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packet Leskage Test Form Revisco 10-01-78 with all deadweight pressures adjusted thereon as well as the flowing temperatures (gas soons only) and gravity and GOR (oil soons only).