

SUNDARY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE APPLICATION FOR PERMIT - "A" (FORM C-101) FOR SUCH PROPOSALS.)

3. Indicate Type of Lease
State ☐ Free ☒

5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO OPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE APPLICATION FOR PERMIT TO DRILL (FORM C-101) FOR SUCH PROPOSALS.)

DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR RE-ENTER EXISTING WELLS. USE APPLICATION FOR PERMIT-LN (FORM C-151) FOR SUCH PROPOSALS.		7. Unit Agreement Name NEBU Agrmt. No. 1, Sec 929	
1. OIL WELL ☐ GAS WELL ☒ OTHER-	8. Form or Lease Name Northeast Blanco Unit		
2. Name of Operator Blackwood & Nichols Company		9. Well No. 63	
3. Address of Operator P.O. Box 1237, Durango, Colorado 81301		10. Field and Pool, or wildcat Blanco Mesaverde	
4. Location of Well UNIT LETTER M 1100 FEET FROM THE South LINE AND 990 FEET FROM			
THE West LINE, SECTION 1 TOWNSHIP 31N RANGE 7W NMPM.			
15. Elevation (Show whether M, RT, GR, etc.) 6559 GL		12. County San Juan	

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:	☐	SUBSEQUENT REPORT OF:
-------------------------	--------------------------	-----------------------

PERFORM REMEDIAL WORK	☐	PLUG AND ABANDON	☐	REMEDIAL WORK	☐	ALTERING CASING	☐
TEMPORARILY ABANDON	☐			COMMENCE DRILLING OPER.	☐	PLUG AND ABANDONMENT	☐
PULL OR ALTER CASING	☐	CHANGE PLANS	☐	CASING TEST AND CEMENT JOB	☒		
OTHER _____	☐			OTHER _____			

17. Describe Proposed or Completed Operations; Clearly state all pertinent facts, and give pertinent dates, including estimated date of starting any proposed work; SEE RULE 1103.

On October 16, 1976, ran 119 jts., 7", K-55, 23# casing; 3669' set at 3683', cemented with 125 sacks of Howco light cement with 1/4# flocele per sack and 2% CaCl_2 followed with 100 sacks class B cement with 1/4# flocele per sack with 2% CaCl_2 . Ran temperature survey top cement 2400'. Tested 7" casing with 1000 PSI for thirty minutes, held OK.

On October 20, 1976 ran 192 jts of 4-1/2", K-55, 10.50# casing; 6060; set at 6072'. Cemented with 225 sacks of class B Cement with 4% gel, .6% CR-2 and 1/4# flocele per sack; followed with 100 sacks of class B cement with .3% HR-4 and 1/4# flocele per sack. Ran temperature survey, top of cement 3150'. Tested casing with 1000 PSI for thirty minutes, held OK.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED DeLasso Loos

District Manager

11-22-76

Original Signed by M. R. Kendrick

APPROVED BY _____

TITL E

DATE _____

CONDITIONS OF APPROVAL, IF ANY: